

Anybus CompactCom 30 Module EtherNet/IP Beacon 2-port

Item number: AB6228-B

The Anybus CompactCom 30 EtherNet/IP Beacon 2-Port is a communication interface that can be embedded into any industrial device or machine to enable communication with EtherNet/IP Beacon networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.



*Enable communication between industrial devices and
EtherNet/IP Beacon networks*

Features and benefits

Anybus CompactCom 30 Module EtherNet/IP Beacon 2-port



General

Net Width (mm)	50
Net Height (mm)	22
Net Depth (mm)	52
Net Weight (g)	28
Packed Weight (g)	28
Operating Temperature °C Min	-40
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	B
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8-bit parallel (30 ns access) UART (max 625kbps)
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M30 module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1

Identification and Status

Product ID	AB6228-B
Successor	AB6604-D
Country of Origin	Sweden

Anybus CompactCom 30 Module EtherNet/IP Beacon 2-port



Identification and Status

HS Code	8517620000
Export Control Classification Number (ECCN)	3A991.a.2
Supply Risk Factor ERP	Used in Volume 01

Physical Features

Connectors / Input / Output	2x RJ45
LED Indicators	Indicates Module Status and Network Status.
Form Factor	Module

Certifications and Standards

Protection Class IP	IP20
UL Information	E214107