

Anybus CompactCom 30 Module Modbus-RTU without housing

The second second

Item number: AB6303-B

The Anybus CompactCom 30 Modbus-RTU without housing is a communication interface that can be embedded into any industrial device or machine to enable communication with Modbus-RTU networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.

Enable communication between industrial devices and Modbus-RTU networks

Features and benefits



Anybus CompactCom 30 Module Modbus-RTU without housing



General	
Net Width (mm)	37
Net Height (mm)	16
Net Depth (mm)	51
Net Weight (g)	19
Packed Weight (g)	19
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	A
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8-bit parallel (30 ns access) UART (max 625kbps)
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M30 module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1

Identification and Status

Product ID	AB6303-B
Country of Origin	Sweden
HS Code	8517620000



Anybus CompactCom 30 Module Modbus-RTU without housing

E214107

UL Information



Identification and Status		
Export Control Classification Number (ECCN)	3A991.a.2	
Supply Risk Factor ERP	Used in Volume 01	
Physical Features		
Connectors / Input / Output	RJ45	
LED Indicators	Indicates Module Status and Network Status.	
Form Factor	Module without Housing	
Certifications and Standards		
Protection Class IP	IP20	

