

Ixxat INpact PIRFO Slave PCIe Mini

Item number: 1.01.0341.26100

The Ixxat INpact PIRFO Slave PCle Mini is a versatile and efficient solution to connect embedded systems and PCs to PROFINET IRT Fiber Optic networks. This preconfigured PIRFO variant features a compact PCle Mini format and provides reliable high-speed and interference-free communication, ideal for electromagnetically noisy environments.



Connects computers and embedded systems to PROFINET Fiber Optic networks

Features and benefits

Ideal for demanding requirements

Offers reliable data processing with deterministic real-time behavior, utilizing Anybus CompactCom NP40 technology to ensure efficient communication in complex and timesensitive applications.

Compact PCIe Mini form factor

With its PCIe Mini form factor, this variant is ideal for small devices and mobile applications with limited available space.

Broad application range

Suitable for diverse applications including slave connection to networks, process data visualization, Human-Machine-Interfaces (HMI), data acquisition, and measurement and analysis.

Seamless PC operation under Windows and Linux

Powerful driver packages enable easy integration into PC-based Ixxat applications and customer-specific programs.

PCIe Mini interface

Single-lane (1x) PCI Express interface supports high-speed data transmission, ideal for demanding industrial applications.

Overvoltage protection

Galvanic isolation safeguards against overvoltage and protects from potential electrical damage.

Easy configuration and maintenance

User-friendly configuration tools simplify setup and system updates, making it a flexible solution for long-term use in dynamic environments.



Ixxat INpact PIRFO Slave PCIe Mini



General	
Isolation	1,500 Vrms
Configuration	The Ixxat INpact cards comes with a comprehensive C-API based driver package for Windows and Linux – enabling simple and rapid development of customer-specific applications. Their uniform application programming interface allows for quick protocol switching with minimal programming, enhancing flexibility and reducing development costs.
Packaging Material	Cardboard

	. .			
lonti	tiooti	α n α	ndli	Status
	111.411	1111 –		11115
 10110	I I O G CI		iia C	latau

Product ID	1.01.0341.26100
Country of Origin	Germany
HS Code	8517620000
Export Control Classification Number (ECCN)	EAR99
Supply Risk Factor ERP	Used in Volume 01
Purchasing Multiple ERP	1

PROFINET Features

PROFINET Supported Functionality

100 Mbit/s Ethernet ports with full duplex operation, event-based interface method enables easy access to input and output data at any time, pre-certified for full interoperability and network compliance, supports up to 128 sub-modules in total, up to 32767 ADIs, Generic and Profinet specific diagnostic support, complies with Profinet IO conformance class C, up to 1440 bytes I/O data in each direction with very low latency, status bytes included, SNMP agent, FTP server, E-mail client, Server Side Include (SSI) functionality, JSON functionality, customizable identity information, GSD file template provided by HMS, Media Redundancy Protocol (MRP)

Certifications and Standards

ETIM Classification	EC000515
WEEE Category	IT and telecommunications equipment

