

## Anybus X-gateway - AS-Interface Master - Interbus CU Slave

Item number: AB7825-F

The Anybus X-gateway AS-Interface Master to Interbus CU Slave enables you to connect any AS-Interface device or equipment to Interbus control systems. It can be used when there is no existing AS-Interface control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



*A protocol converter that connects AS-Interface devices to Interbus CU PLCs*

### Features and benefits

- ✓ **Reach new markets**

Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- ✓ **Slim hardware design**

The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **Easy configuration – No programming required!**

Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- ✓ **Trusted partner**

Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.
- ✓ **No PLC card slot needed**

The gateway does not use a card slot in the control system, leaving room for other equipment.
- ✓ **3-year warranty**

The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✓ **Increased PLC performance**

The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.
- ✓ **Life cycle management**

HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.
- ✓

# Anybus X-gateway - AS-Interface Master - Interbus CU Slave



| General  |                                    |
|--|------------------------------------|
| Net Width (mm)                                 | 44                                 |
| Net Height (mm)                                | 127                                |
| Net Depth (mm)                                 | 114                                |
| Net Weight (g)                                 | 400                                |
| Packed Width (mm)                              | 17                                 |
| Packed Height (mm)                             | 9                                  |
| Packed Depth (mm)                              | 19                                 |
| Packed Weight (g)                              | 600                                |
| Operating Temperature °C Min                   | -25                                |
| Operating Temperature °C Max                   | 65                                 |
| Storage Temperature °C Min                     | -40                                |
| Storage Temperature °C Max                     | 85                                 |
| Current Consumption Type Value at Vcc Nom (mA) | 200mA @ 24V DC                     |
| Current Consumption Max value at Vcc nom (mA)  | 400mA @ 24V DC                     |
| Input Voltage (V)                              | 24V DC (-20% to +20%)              |
| Power Connector                                | 2-pin, 5.08 Phoenix plug connector |
| Isolation                                      | TRUE                               |
| Mounting                                       | DIN-rail (EN 50022 standard)       |
| Housing Materials                              | Aluminum, Plastic                  |

# Anybus X-gateway - AS-Interface Master - Interbus CU Slave



## General

|                    |           |
|--------------------|-----------|
| Packaging Material | Cardboard |
|--------------------|-----------|

## Identification and Status

|   |                        |
|---|------------------------|
| Product ID                                  | AB7825-F               |
| Country of Origin                           | Sweden                 |
| HS Code                                     | 8517620000             |
| Export Control Classification Number (ECCN) | 5A991.b.4b             |
| Supply Risk Factor ERP                      | Volume not defined yet |

## Physical Features

|                             |  |
|-----------------------------|--|
| Connectors / Input / Output | 1x D-sub 9-pin male and 1x D-sub 9-pin female, USB-B Config port |
|-----------------------------|--|

## INTERBUS Features

|                                  |   |
|----------------------------------|---|
| INTERBUS Mode                    | Slave   |
| INTERBUS Supported Functionality | EN 50170; PCP V.2.0. (0, 1, 2, or 4 words); Automatic slave address detection |
| INTERBUS Baud Rate               | 500 kbit/s â€” 2 Mbit/s   |
| INTERBUS Input Data Size         | 20 bytes of process data (512 bytes with PCP)                                 |
| INTERBUS Output Data Size        | 20 bytes of process data (512 bytes with PCP)                                 |

## Certifications and Standards

|                     |  |
|---------------------|--|
| Protection Class IP | IP20   |
| Recycle / Disposal  | TRUE   |
| UL Information      | E214107: Ord.Loc UL508, CSA C22.2 NO. 142  |
| Environment         | EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6 |
| WEEE Category       | IT and telecommunications equipment  |