



Anybus Wireless Bolt CAN

Item number: AWB2021-B-10PACK

The Anybus Wireless Bolt Serial connects CAN-based machines to wireless networks via Bluetooth® or Wi-Fi. Designed for multi-directional applications, it's ideal for establishing wireless connections with roaming machines, such as AGVs or control cabinets from any angle.



Anybus 无线 CAN

任何 CAN 设备均可通过蓝牙或 Wi-Fi 连接到 Anybus 无线 CAN 设备。

任何 CAN 设备均可通过蓝牙或 Wi-Fi 连接到 Anybus 无线 CAN 设备。

特点和优势

- **低总拥有成本**
由于集成天线和通信模块的设计，无需购买额外的天线或配件。
- **灵活的 CAN 数据管理**
最多可配置 28 个可自由调整的 CAN 接收滤波器，提供对传入 CAN 消息的精确控制，以实现定制化和高效的通信。
- **多功能波特率支持**
支持广泛的波特率范围（10 到 1000 kbps），并允许在多节点网络中进行个性化配置，以实现最佳性能和适应不同的通信需求。
- **专为多方向应用设计**
非常适合建立与漫游机器（如 AGV）或从任意角度控制柜的无线连接。
- **快速启动和高确定性**
非常适合连接需要短启动时间和高确定性的现场级设备。
- **易于访问数据**
无线连接到 Anybus Bolt 并轻松访问机器或控制柜。无需配置 PLC 或机器，无需停机或阻碍生产。
- **CAN 到 TCP/IP 数据转换**
将 CAN 2.0A/B（11/29 位标识符）数据转换为 TCP/IP，支持 J1939 和 CANopen 等协议，并实现任何 CAN 协议的透明传输。
- **一体化无线通信**
一体化设计，集成了连接器、通信处理器和集成天线。选择白色顶部的 Sunbolt 选项，可提供 30% 更好的保护，防止更高的温度。
- **易于安装**
直接将无线 Bolt 安装在控制柜或机器上，使其看起来像是安装的一部分。或者使用 Bolt 底座保护器安装套件将其安装在杆、墙或类似位置。
- **易于配置**
得益于直观的基于网络的界面，可在几秒钟内建立无线连接。

Connect CAN machines in multi-directional applications via Bluetooth or Wi-Fi

Features and benefits

- ✓ **Low total cost of ownership**
Thanks to the integrated design of the antenna and communication module, there's no need for additional antenna or accessory purchases.
- ✓ **Flexible CAN data management**
Customize your data with up to 28 freely adjustable CAN receive pass-through filters, providing precise control over incoming CAN messages for tailored and efficient communication.
- ✓ **Versatile baud rate support**
Supports a wide range of baud rates (10 to 1000 kbps) and allows individual customization in multi-node networks for optimal performance and adaptation to diverse communication needs.
- ✓ **Designed for multi-directional applications**
Ideal for establishing wireless connections to roaming machines, such as AGVs, or to control cabinets from any angle.
- ✓ **Easy access to data**
Wirelessly connect to the Anybus Bolt and easily access the machine or cabinet. Configure the PLC or machine without halting or hindering production.
- ✓ **Quick start up and high determinism**
Ideal for connecting field-level devices that require short start-up times and high determinism.
- ✓ **All-in-one wireless communication**
All-in-one package featuring a connector, communication processor, and integrated antenna in the same unit. Choose the white top Sunbolt option for 30% better protection against higher temperatures.
- ✓ **CAN to TCP/IP data conversion**
Converts CAN 2.0A/B (11/29-bit identifier) data to TCP/IP, supporting protocols such as J1939 and CANopen, and enables the transparent transfer for any CAN protocol.
- ✓ **Industrial design**
Withstands harsh environments due to its IP66/67-rated enclosure and wide operating temperature range. Choose the white top Sunbolt option for 30% better protection against higher temperatures.
- ✓ **Easy to install**
Attach the Wireless Bolt directly onto cabinets or machines to look like an integrated part of the installation. Or use the Bolt Base Protector mounting kit to install it on a pole, wall, or similar.
- ✓ **Easy to configure**
Establish a wireless connection in seconds thanks to the intuitive web-based interface.





Anybus Wireless Bolt CAN

General

Net Weight (g)	940
Net Dimensions (mm)	68 x 75 (Ø X H) Height above mounting surface: 42.
Packed Weight (g)	940
Operating Temperature °C Min	-40
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Power Consumption (W)	1.7
Input Voltage (V)	9-30
Power Connector	3-pole
Housing Materials	Plastic
Packaging Material	Cardboard

Identification and Status

Product ID	AWB2021-B-10PACK
Model Code	AWB2AC
Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	5A992.c
Supply Risk Factor ERP	Volume not defined yet

Physical Features

Connectors / Input / Output	RJ45, 3-pole screw connection
-----------------------------	-------------------------------



Anybus Wireless Bolt CAN

Wi-Fi Features

Operation Mode	Access Point, Client
RF Output Power	18 dBm EIRP (including antenna gain 3dBi)
Max No. Of Connections, Access Point	7
Security	WPA2 Personal; WPA2 Enterprise
Net Data Throughput	20 Mbps

Bluetooth Features

Operation Mode	Access Point, Client
Max No. Of Connections	7
Bluetooth Version	Classic Bluetooth v2.1
Net Data Throughput	20 Mbps

Bluetooth Low Energy Features

Operation Mode (LE)	Access Point, Client
RF Output Power (LE)	14 dBm EIRP (including max antenna gain 3 dBi)
Max No. Of Connections (LE)	7
Bluetooth Version (LE)	Bluetooth v4.0
Net Data Throughput (LE)	1Mbps

Certifications and Standards

Protection Class IP	IP66, IP67
Vibration and Shock	Sinosodial vibration test according to IEC 60068-2-6:2007 and with extra severities; Number of axes: 3 mutually perpendicular (X:Y:Z), Duration: 10 sweep cycles in each axes, Velocity: 1 oct/min, Mode: in operation, Frequency: 5-500 Hz, Displacement ±3.5 mm, Acceleration: 2g. Shock test according to IEC 60068-2-27:2008 and with extra severities; Wave shape: half sine, Number of shocks: ±3 in each axes, Mode: In operation, Axes ± X,Y,Z, Acceleration: 30 m/s ² , Duration: 11 ms.
Environment	EN 61000-6-2:2019 EN 61000-4-2:2009 EN 61000-4-3:2006 + A1:2008 + A2:2010 EN 61000-4-4:2012 EN 61000-4-5:2014 EN 61000-4-6:2014 EN 61000-6-4:2019 EN 55016-2-3:2017 EN 55032:2015 EN 301 489-1 V2.2.3 EN 301 489-17 V3.1.1
WEEE Category	IT and telecommunications equipment

