

Ewon Flexy extension card - IO (8DI-4AI-2DO)

Item number: FLX3402_00

This card enhances Ewon Flexy's connectivity with an IO connection. The Flexy I/O card offers eight digital inputs, four configurable analogue inputs, and two digital outputs. Ideal for OEMs and system integrators, it facilitates data transfer from remote locations to central servers. Compatible with Ewon Flexy 10x, 20x series and 205.



Interchangeable extension card for enhanced connectivity

Features and benefits

✓ **Build your own Flexy gateway**

Keep up with the evolution of communication technologies while protecting your investment in the device! The Ewon Flexy extension cards make this gateway highly modular and flexible.

Ewon Flexy extension card - IO (8DI-4AI-2DO)



General	
Net Width (mm)	22
Net Height (mm)	79
Net Depth (mm)	84
Net Weight (g)	50
Packed Width (mm)	102
Packed Height (mm)	30
Packed Depth (mm)	95
Packed Weight (g)	72.5
Operating Temperature °C Min	-25
Operating Temperature °C Max	+60
Storage Temperature °C Min	-30
Storage Temperature °C Max	+70
Relative Humidity	10 to 95% relative humidity (non-condensing).
Isolation	Analogue inputs: 1.5kV from power supply Digital inputs: 1.5 kV from electronic AND power supply Output relays (NO): 1.5 kV from electronic AND power supply
Content of Delivery	This product consists of the following components: an electronic extension board inserted in a plastic front plate with an IO connector and packed in an ESD plastic bag sealed with a yellow sticker, legal references in paper version and a cardboard box.
Housing Materials	Plastic
Packaging Material	Cardboard
Warranty (years)	3
Identification and Status	
Product ID	FLX3402_00

Ewon Flexy extension card - IO (8DI-4AI-2DO)



Identification and Status

Model Code	02701
Country of Origin	Belgium
HS Code	8517790000
Export Control Classification Number (ECCN)	5A992.c
Supply Risk Factor ERP	Used in Volume 01
Purchasing Multiple ERP	90

Physical Features

Connectors / Input / Output	4x Analogue inputs: Voltage mode 0-10V, 16 bit resolution or current mode, 4-20mA, user selectable with Dip Switch configuration 8x Digital inputs: 0 to 12/24 VDC 2x Output relays (NO): 2A/30V, VAC/VDC
-----------------------------	---

Certifications and Standards

Environment	Temperature - Operating & Storage tested according to: IEC 60068-2-1 Cold test, IEC 60068-2-2 Dry heat test, IEC 60068-2-14 Change of temperature, IEC 60068-2-30 Cyclic damp heat test
Vibration and Shock	Vibration & shocks tested according to: IEC 60068-2-27 Bumps, IEC 60068-2-64 Vibration (broad-band random), IEC 60068-2-6 Vibration (sinusoidal)
WEEE Category	IT and telecommunications equipment
Other Certification	Giteki Japan