

Anybus EtherNet/IP to PROFIBUS Linking Device

Item number: HMS-EN2PB-R

The Anybus EtherNet/IP to PROFIBUS Linking Device converts PROFIBUS to EtherNet/IP, enabling you to connect any PROFIBUS device to a Logix PLC control system. The linking device presents PROFIBUS data as easily processed I/O data, offloading the PLC from working with extra calculations and allowing for seamless integration with Studio 5000.



Enable seamless integration of serial devices to Studio 5000

Features and benefits

✓ **Seamless integration with Studio 5000**

The unique Studio 5000[®] Logix designer integration provides access to everything, including serial network configuration. No need for extra 3rd-party software, licenses, or programming.

✓ **Automatic tag names**

Our Custom Add-On Profile for Studio 5000 supports the automatic generation of named and structured controller tags, eliminating the need to create alias tags.

✓ **No programming required**

Easy to set up with the Custom Add-On Profile. No programming required!

✓ **Trusted partner**

Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.

✓ **Life cycle management**

HMS maintains every part of the Linking Devices, including network updates, throughout the product's lifecycle.

✓ **Connect, configure, done**

EtherNet/IP Linking Devices are configured using a Custom Add-On Profile in Studio 5000, dynamically generating data structures for each device and eliminating the need for ladder logic files.

✓ **3-year warranty**

The linking devices are designed to be robust and long-lasting. A 3-year guarantee is provided.

✓ **Increased performance - Logix PLC**

Presents serial data as easily processed I/O data offloading the Logix PLC from extra calculations.

✓ **Life cycle management**

HMS maintains every part of the Linking Devices, including network updates, throughout the product's lifecycle.



Anybus EtherNet/IP to PROFIBUS Linking Device

General	
Net Width (mm)	35
Net Height (mm)	110
Net Depth (mm)	101
Net Weight (g)	155
Packed Width (mm)	14
Packed Height (mm)	6
Packed Depth (mm)	17
Packed Weight (g)	320
Operating Temperature °C Min	-25
Operating Temperature °C Max	60
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	300mA @ 24V DC
Input Voltage (V)	24V DC (-15% to +20%)
Power Connector	3-pin, 5.08 Phoenix plug connector
Isolation	TRUE
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	PC ABS, UL 94 VO



Anybus EtherNet/IP to PROFIBUS Linking Device

General

Packaging Material	Cardboard
--------------------	-----------

Identification and Status

Product ID	HMS-EN2PB-R
Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	5A991.b.1
Supply Risk Factor ERP	Used in Volume 01

Physical Features

Connectors / Input / Output	1x D-sub 9-pin female PROFIBUS connector, 2xRJ45
-----------------------------	--

EtherNet/IP Features

EtherNet/IP Mode	Adapter / Slave
EtherNet/IP Supported Functionality	Preinstalled Add On Profile in Studio 5000 Logix Designer
EtherNet/IP Configuration File	EDS available
EtherNet/IP Bandwidth	10/100MBit
EtherNet/IP Input Data Size	3500 bytes over 10 connections
EtherNet/IP Output Data Size	3500 bytes over 10 connections

PROFIBUS Features

PROFIBUS Mode	Master
PROFIBUS Supported Functionality	PROFIBUS DP Master functionality according to IEC 61158;Acyclic Communication (DP-V1, Class 1 & 2);LiveList;ControlStatus
PROFIBUS Device Address	0-125
PROFIBUS No. Of Devices	125
PROFIBUS Baud Rate	9600 bit/s - 12 Mbit/s
PROFIBUS Input Data Size	3500 bytes



Anybus EtherNet/IP to PROFIBUS Linking Device

PROFIBUS Features

PROFIBUS Output Data Size	3500 bytes
----------------------------------	------------

Certifications and Standards

Protection Class IP	IP20
Recycle / Disposal	TRUE
UL Information	E214107: Ord.Loc UL 61010-1, UL 61010-2-201, CSA C22.2 NO. 61010-1-12, CSA C22.2 NO. 61010-2-201:14; E203225: Haz.Loc CL I DIV2 GP A,B,C,D T4, ANSI/ISA 12.12.01, CAN/CSA C22.2 No. 213-15
ATEX Information	II 3 G Ex nA IIC T4 Gc, EN IEC 60079-0; EN 60079-15
Environment	EN 61000-6-4, EN 55016-2-3 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment