

## Anybus CompactCom 40 Brick BACnet/IP

Item number: AB6682-D

The Anybus CompactCom 40 BACnet/IP is a communication interface that can be embedded into any industrial device or machine to enable communication with BACnet/IP networks. The pluggable design enables integration late in the assembly process, the addition of specific network connectors, and compliance with protection class requirements.



*Enable communication between industrial devices and BACnet/IP networks*

### Features and benefits

- ✓ **High performance**  
Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.
- ✓ **Quick time to market**  
HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.
- ✓ **Life cycle management**  
HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.
- ✓ **Fully embedded – meet IP requirements**  
The brick can be fully embedded within your product, conserving valuable space, and enabling you to provide IP class-certified protection.
- ✓ **Supports hardware changes**  
Possible to swap or install late in the manufacturing process.
- ✓ **Versatile Event-Based Hardware Interfaces**  
Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.
- ✓ **Pre-certified**  
Pre-certified for BACnet/IP network compliance, enabling faster network certification. Version 1.14.
- ✓ **Design flexibility**  
Add your own connectors and peripherals, offering design flexibility that matches your unique needs.
- ✓ **Robust Security Measures**  
Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.

# Anybus CompactCom 40 Brick BACnet/IP



## General

Net Weight (g)	10
Packed Weight (g)	10
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8/16-bit parallel (30 ns access) High speed SPI, baudrate configurable up to 20 MHz I/O (shift register interface, cyclical update time 82 µs) UART (for backwards compatibility with 30-series, max 625kbps)
Content of Delivery	CompactCom B40 module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1 year

## Identification and Status

Product ID	AB6682-D
Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	EAR99
Supply Risk Factor ERP	Volume not defined yet

## Physical Features

Form Factor	Brick (pluggable)
-------------	-------------------

## Certifications and Standards

UL Information	E214107
----------------	---------