

## Anybus Communicator – Serial Master to EtherNet/IP adapter

Item number: ABC3007-A

The Anybus Communicator Serial Master to EtherNet/IP enables you to connect any RS-232/485 device or equipment to EtherNet/IP control systems. Anybus Communicators ensure reliable, secure, and high-speed data transfers between different industrial networks. Thanks to our intuitive web-based user interface, they're also incredibly easy to use.



*A protocol converter that connects serial devices to EtherNet/IP control systems*

### Features and benefits

- ✓ **Intuitive user interface**  
Use the intuitive web-based user interface to easily configure the Communicator via the drag-and-drop functionality or to analyze live data, export log files, and generate support packages.
- ✓ **High performance**  
Powered by the award-winning NP40 network processor and high-end components, the Communicator meets the constantly growing demand for more data to be transferred faster.
- ✓ **Instant data transfer**  
Instant data transfer lets you take advantage of high-speed industrial networks, as the Communicator provides hardware-accelerated endian conversion (byte swap), saving processing time on the PLC.
- ✓ **Convert standard and proprietary serial protocols**  
Convert standard serial protocols such as Modbus RTU and proprietary serial request/response or produce/consume-based protocols.
- ✓ **Brand Labeling**  
Pre-configure the Communicator and customize the hardware and user interface with your colors and logos.
- ✓ **Cybersecurity**  
The secure boot protects against malware, while a security switch locks configurations to prevent unauthorized changes. Ports used in production are disabled to add another layer of security.
- ✓ **Optimized hardware design**  
The Communicator has forward-facing ports and is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **5-year warranty**  
Thanks to carefully selected industrial components the Communicator operates reliably in harsh environments, ensuring uptime and longevity. Our confidence in quality is reflected in a 5-year warranty.
- ✓ **Instant diagnostics**  
The user interface displays real-time connection status and I/O data mapping for easy troubleshooting. Easily generate a support file containing all the necessary information.
- ✓ **Life cycle management**  
HMS maintains every part of the Communicator, including network updates, throughout the product's lifecycle.

# Anybus Communicator – Serial Master to Ethernet/IP adapter



General	
Net Width (mm)	27
Net Height (mm)	144
Net Depth (mm)	98
Net Weight (g)	150
Packed Width (mm)	15
Packed Height (mm)	6
Packed Depth (mm)	17
Packed Weight (g)	185
Operating Temperature °C Min	-25
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	90mA @ 24V DC (2.2W)
Current Consumption Max value at Vcc nom (mA)	125mA @24V DC (3W)
Input Voltage (V)	12-30V DC
Power Connector	3-pin, 5.08 Phoenix plug connector
Isolation	TRUE
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	PC ABS, UL 94 VO

# Anybus Communicator – Serial Master to Ethernet/IP adapter



## General

Packaging Material	Cardboard
Warranty (years)	5

## Identification and Status

Product ID	ABC3007-A
Model Code	40-SER-ETH-B
Predecessor	AB7072-B, AB7072-B-5PACK, AB7007-C, AB7007-C-5PACK
Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	5A991.b.1

## Physical Features

Connectors / Input / Output	1x 7-pin, 5.08 Phoenix plug connector, 2xRJ45, RJ45 Config port
Push Buttons	Factory reset

## EtherNet/IP Features

EtherNet/IP Mode	Adapter / Slave
EtherNet/IP Supported Functionality	Endian conversion (byte swap); QoS; Ethernet/IP Class 1 and 3; Quick Connect Class B; DLR (beacon mode); Daisy Chainging; CT19 ODVA Conformance
EtherNet/IP Configuration File	EDS available
EtherNet/IP Bandwidth	10/100MBit down to 1ms cycle time
EtherNet/IP Input Data Size	1448 bytes
EtherNet/IP Output Data Size	1448 bytes

## Modbus-RTU Features

Modbus-RTU Mode	Client / Master
Modbus-RTU Supported Functionality	RS-232; RS485; Standard Modbus RTU Master; Custom Request / Responce commands; Custom Produce / Consume transactions; Trigger initated transactions; 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze
Modbus-RTU Functions Supported	1, 2, 3, 4, 5, 6, 7, 8, 11, 12, 15, 16, 17, 20, 21, 22, 24

# Anybus Communicator – Serial Master to Ethernet/IP adapter



## Modbus-RTU Features

<b>Modbus-RTU Baud Rate</b>	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600,115200,128000 bit/s
<b>Modbus-RTU Input Data Size</b>	1500 bytes
<b>Modbus-RTU Output Data Size</b>	1500 bytes

## Serial Features

<b>Max Stations</b>	31
<b>Connector</b>	1x 7-pin, 5.08 Phoenix plug connector
<b>Max Nodes</b>	31
<b>Ports</b>	1 x RS232/RS485
<b>Baud Rate</b>	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600,115200,128000 bit/s
<b>Supported Functionality</b>	RS-232; RS485; Standard Modbus RTU Master; Custom Request / Response commands; Custom Produce / Consume transactions; Trigger initiated transactions; 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze

## Certifications and Standards

<b>Protection Class IP</b>	IP20
<b>UL Information</b>	E214107: Ord.Loc UL 61010-1, CSA C22.2 No. 61010-1, UL 61010-2-201, CSA C22.2 No. 61010-2-201
<b>ATEX Information</b>	II 3 G Ex ec IIC T4 Gc, EN IEC 60079-0, 60079-7, IEC 60664-1
<b>Environment</b>	EN 55016-2-3 Class A, EN 55032 Class A, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
<b>WEEE Category</b>	IT and telecommunications equipment