

Anybus CompactCom 40 Module EtherNet/IP IloT Secure



Item number: AB6651-C

Anybus CompactCom 40 EtherNet/IP IloT Secure is a communication interface that can be embedded into any industrial device or machine to enable communication with EtherNet/IP and IloT protocols. It exchanges data with PLCs but uses OPC UA or MQTT to transmit data to IT systems. The module version includes connectors for a fast time to market.

Enable communication between industrial devices, EtherNet/IP & IloT protocols

Features and benefits

- ✓ **High performance**
Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.
- ✓ **Quick time to market**
HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.
- ✓ **Life cycle management**
HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.
- ✓ **Easy to install**
Installing the Anybus CompactCom module is a breeze—simply slide it into the host slot. This user-friendly process can be completed by the end-user.
- ✓ **Reap the benefits of IloT**
Use OPC UA or MQTT to easily pass data to higher-level systems for analysis and reap the benefits of IloT, such as predictive maintenance or optimization of devices and machines.
- ✓ **Supports hardware changes**
Possible to swap or install late in the manufacturing process.
- ✓ **Versatile Event-Based Hardware Interfaces**
Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.
- ✓ **ODVA pre-certified**
Pre-certified with ODVA for network compliance, enabling faster network certification.
- ✓ **Complete communication interface**
The Anybus CompactCom module is a complete communication interface, equipped with connectors that simplify integration. Enjoy an all-in-one solution with easy interchangeability.
- ✓ **Robust Security Measures**
Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.
- ✓ **Advanced security measures**
Prioritizing security, it incorporates IEEE 802.1AR compliance, a security chip, secure boot, root of trust, and employs secure protocols for encrypting data exchanges.

Anybus CompactCom 40 Module EtherNet/IP IIoT Secure



General	
Net Width (mm)	50
Net Height (mm)	22
Net Depth (mm)	52
Net Weight (g)	35
Packed Width (mm)	8
Packed Height (mm)	3
Packed Depth (mm)	7
Packed Weight (g)	35
Operating Temperature °C Min	-40
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	B
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8/16-bit parallel (30 ns access) High speed SPI, baudrate configurable up to 20 MHz I/O (shift register interface, cyclical update time 82 µs) UART (for backwards compatibility with 30-series, max 625kbps)
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M40 module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1 year

Anybus CompactCom 40 Module EtherNet/IP IIoT Secure



Identification and Status

Product ID	AB6651-C
Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	EAR99

Physical Features

Connectors / Input / Output	2x RJ45
LED Indicators	Integrated on front. Indicates Module Status, Network Status and Link/Activity.
Form Factor	Module

Certifications and Standards

UL Information	E214107
----------------	---------