

Anybus X-gateway - AS-Interface Master - EtherNet/IP Adapter

Item number: AB7820-F

The Anybus X-gateway AS-Interface Master to EtherNet/IP Adapter enables you to connect any AS-Interface device or equipment to EtherNet/IP control systems. It can be used when there is no existing AS-Interface control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



A protocol converter that connects AS-Interface devices to EtherNet/IP PLCs

Features and benefits

- ✓ **Reach new markets**

Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- ✓ **Slim hardware design**

The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **Easy configuration – No programming required!**

Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- ✓ **Trusted partner**

Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.
- ✓ **No PLC card slot needed**

The gateway does not use a card slot in the control system, leaving room for other equipment.
- ✓ **3-year warranty**

The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✓ **Increased PLC performance**

The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.
- ✓ **Life cycle management**

HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.
- ✓

Anybus X-gateway - AS-Interface Master - Ethernet/IP Adapter



General

Net Width (mm)	44
Net Height (mm)	127
Net Depth (mm)	114
Net Weight (g)	400
Packed Width (mm)	17
Packed Height (mm)	9
Packed Depth (mm)	19
Packed Weight (g)	750
Operating Temperature °C Min	-25
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	400mA @ 24V DC
Input Voltage (V)	24V DC (-20% to +20%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Isolation	TRUE
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Aluminum, Plastic

Anybus X-gateway - AS-Interface Master - Ethernet/IP Adapter



General

Packaging Material	Cardboard
--------------------	-----------

Identification and Status

Product ID	AB7820-F
Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	5A991.b.1
Supply Risk Factor ERP	Used in Volume 01

Physical Features

Connectors / Input / Output	2xRJ45, USB-B Config port
-----------------------------	---------------------------

EtherNet/IP Features

EtherNet/IP Mode	Adapter / Slave
EtherNet/IP Supported Functionality	EtherNet/IP Level 2 I/O Server CIP; Daisy Chainging; QoS; DNS
EtherNet/IP Configuration File	EDS available
EtherNet/IP Bandwidth	10/100MBit
EtherNet/IP Input Data Size	509 bytes
EtherNet/IP Output Data Size	505 bytes

Certifications and Standards

Protection Class IP	IP20
Recycle / Disposal	TRUE
UL Information	E214107: Ord.Loc UL508, CSA C22.2 NO. 142
Environment	EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment