

# Anybus X-gateway - Modbus TCP Client - PROFINET-IO Device

Item number: AB9007-B-5PACK

The Anybus X-gateway Modbus TCP Client to PROFINET-IO Device enables you to connect any Modbus TCP device or equipment to PROFINET-IO control systems. It can be used when there is no existing Modbus TCP control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



*A protocol converter that connects Modbus TCP devices to PROFINET-IO PLCs*

## Features and benefits

- ✔ **Reach new markets**

Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- ✔ **Slim hardware design**

The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✔ **Easy configuration – No programming required!**

Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- ✔ **Powerful**

Up to 512 bytes of Input and Output data in each direction.
- ✔ **Life cycle management**

HMS maintains every part of the gateway, including network updates, throughout the product’s lifecycle.
- ✔ **No PLC card slot needed**

The gateway does not use a card slot in the control system, leaving room for other equipment.
- ✔ **3-year warranty**

The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✔ **Increased PLC performance**

The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.
- ✔ **Trusted partner**

Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.

# Anybus X-gateway - Modbus TCP Client - PROFINET-IO Device



## General

Net Width (mm)	35
Net Height (mm)	110
Net Depth (mm)	101
Net Weight (g)	820
Packed Weight (g)	820
Operating Temperature °C Min	-25
Operating Temperature °C Max	60
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	150mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	300mA @ 24V DC
Input Voltage (V)	24V DC (-15% to +20%)
Power Connector	3-pin, 5.08 Phoenix plug connector
Isolation	TRUE
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Plastic
Packaging Material	Cardboard

## Identification and Status

Product ID	AB9007-B-5PACK
Successor	ABC3213-A, ABC3290-A, ABC3290EX-A

# Anybus X-gateway - Modbus TCP Client - PROFINET-IO Device



## Identification and Status

Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	5A991.b.1
Supply Risk Factor ERP	Used in Volume 01

## Physical Features

Connectors / Input / Output	2xRJ45, 2x RJ45
-----------------------------	-----------------

## Modbus-TCP Features

Modbus-TCP Mode	Master / Client
Modbus-TCP Supported Functionality	Modbus specification V1.1B; Endian Conversion (Byte swap); LiveList; ControlStatus
Modbus-TCP No. Of Servers	64 transactions
Modbus-TCP Functions Supported	1, 2, 3, 4, 5, 6, 15, 16, 23
Modbus-TCP Bandwidth	10/100 Mbit/s down to 10ms
Modbus-TCP Input Data Size	256 bytes
Modbus-TCP Output Data Size	256 bytes

## PROFINET Features

PROFINET Mode	Slave
PROFINET Supported Functionality	Soft Real-Time (RT); Max 64 slots / 8 sub-slot
PROFINET Configuration File	GSDML available
PROFINET Bandwidth	100Mbit full duplex down to 2ms
PROFINET Input Data Size	256 bytes
PROFINET Output Data Size	256 bytes

## Certifications and Standards

Protection Class IP	IP20
---------------------	------

# Anybus X-gateway - Modbus TCP Client - PROFINET-IO Device



## Certifications and Standards

<b>Recycle / Disposal</b>	TRUE
<b>UL Information</b>	E214107: Ord.Loc UL 61010-1, UL 61010-2-201, CSA C22.2 NO. 61010-1-12, CSA C22.2 NO. 61010-2-201:14; E203225: Haz.Loc CL I DIV2 GP A,B,C,D T4, ANSI/ISA 12.12.01, ANSI/ISA 12.12.01
<b>ATEX Information</b>	II 3 G Ex nA IIC T4 Gc, EN IEC 60079-0; EN 60079-15
<b>Environment</b>	EN 61000-6-4, EN 55016-2-3 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
<b>WEEE Category</b>	IT and telecommunications equipment