

## Anybus X-gateway – CC-Link Slave - Modbus RTU Slave

Item number: AB7621-F

The Anybus X-gateway CC-Link Slave to Modbus RTU Slave enables you to connect any CC-Link system to any Modbus RTU control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



*A protocol converter that connects CC-Link and Modbus RTU control systems*

### Features and benefits

- ✓ **Reach new markets**  
Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- ✓ **Slim hardware design**  
The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **Easy configuration – No programming required!**  
Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- ✓ **Trusted partner**  
Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.
- ✓ **No PLC card slot needed**  
The gateway does not use a card slot in the control system, leaving room for other equipment.
- ✓ **3-year warranty**  
The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✓ **Increased PLC performance**  
The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.
- ✓ **Life cycle management**  
HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.
- ✓

# Anybus X-gateway – CC-Link Slave - Modbus RTU Slave



General	
Net Width (mm)	44
Net Height (mm)	127
Net Depth (mm)	114
Net Weight (g)	400
Packed Width (mm)	17
Packed Height (mm)	9
Packed Depth (mm)	19
Packed Weight (g)	600
Operating Temperature °C Min	-25
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	400mA @ 24V DC
Input Voltage (V)	24V DC (-20% to +20%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Isolation	TRUE
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Aluminum, Plastic

# Anybus X-gateway – CC-Link Slave - Modbus RTU Slave



## General

Packaging Material	Cardboard
--------------------	-----------

## Identification and Status

Product ID	AB7621-F
Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	5A991.b.4b
Supply Risk Factor ERP	Used in Volume 01

## Physical Features

Connectors / Input / Output	1x D-sub 9-pin female, 1x 5-pin, 5.08 Phoenix plug connector, USB-B Config port
DIP & Rotary Switches	dip switch Termination and configuraiton, 3x Rotary CAN Address + Baudrate

## CC-Link Features

CC-Link Mode	Slave
CC-Link Supported Functionality	CC-Link slave Version 1 and 2; Transparent CC-Link; PLC Profile compliant; 4 occupied stations; 8 extension cycles
CC-Link Configuration File	CSP available
CC-Link Output Data Size	896 bits/128 words (368 bytes)
CC-Link Input Data Size	896 bits/128 words (368 bytes)

## Modbus-RTU Features

Modbus-RTU Mode	Slave mode
Modbus-RTU Supported Functionality	Modbus-RTU compliant passive slave node operation; 256 Modbus registers in each direction; Modbus diagnostics
Modbus-RTU Functions Supported	1, 2, 3, 4, 5, 6, 15, 16, 22, 23
Modbus-RTU Baud Rate	1200bps - 57600bps
Modbus-RTU Input Data Size	512 bytes
Modbus-RTU Output Data Size	512 bytes

# Anybus X-gateway – CC-Link Slave - Modbus RTU Slave



## Certifications and Standards

<b>Protection Class IP</b>	IP20
<b>Recycle / Disposal</b>	TRUE
<b>UL Information</b>	E214107: Ord.Loc UL508, CSA C22.2 NO. 142
<b>Environment</b>	EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
<b>WEEE Category</b>	IT and telecommunications equipment

