

## Anybus CompactCom 40 Module Without Housing - PROFINET Fiber Optic - Transparent Ethernet



Item number: AB6736-C

The Anybus CompactCom 40 PROFINET-IRT - Transparent Ethernet is a communication interface that can be embedded into any industrial device or machine to enable communication with PROFINET networks. The Transparent Ethernet channel lets you utilize high-end processors for custom IT functions. The module includes connectors for a fast time to market.

*Enable communication between industrial devices and PROFINET Fiber networks*

### Features and benefits

- ✓ **High performance**  
Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.
- ✓ **Quick time to market**  
HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.
- ✓ **Life cycle management**  
HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.
- ✓ **Custom look**  
Delivered without housing, enabling the Anybus CompactCom to be securely integrated behind the front panel of your device, resulting in a customized appearance and seamless design integration.
- ✓ **Transparent Ethernet channel**  
Includes a Transparent Ethernet channel, allowing users to tap into the potential of their high-end processors for developing personalized IT functions.
- ✓ **Versatile Event-Based Hardware Interfaces**  
Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.
- ✓ **PNO pre-certified**  
Pre-certified with PNO for network compliance, enabling faster network certification.
- ✓ **Complete communication interface**  
The Anybus CompactCom module is a complete communication interface, equipped with connectors that simplify integration. Enjoy an all-in-one solution with easy interchangeability.
- ✓ **Robust Security Measures**  
Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.
- ✓ **Supports hardware changes**  
Possible to swap or install late in the manufacturing process.

# Anybus CompactCom 40 Module Without Housing - PROFINET Fiber Optic - Transparent Ethernet



General	
Net Width (mm)	37
Net Height (mm)	17
Net Depth (mm)	51
Net Weight (g)	34
Packed Weight (g)	34
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	C
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8/16-bit parallel (30 ns access) High speed SPI, baudrate configurable up to 20 MHz I/O (shift register interface, cyclical update time 82 µs) UART (for backwards compatibility with 30-series, max 625kbps)
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M40 module (without housing)
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1 year
Identification and Status	
Product ID	AB6736-C
Country of Origin	Sweden
HS Code	8517620000

# Anybus CompactCom 40 Module Without Housing - PROFINET Fiber Optic - Transparent Ethernet



## Identification and Status

Export Control Classification Number (ECCN)	EAR99
Supply Risk Factor ERP	Volume not defined yet

## Physical Features

Connectors / Input / Output	2x duplex SC-RJ female
LED Indicators	Semi-Integrated. Link/Activity are available on RJ45 connectors. Module Status, Network Status and Link/Activity via application interface or external light pipes
Form Factor	Module without Housing

## Certifications and Standards

UL Information	E214107
----------------	---------