

Anybus CompactCom 30 Module EtherNet/IP

Item number: AB6214-B

The Anybus CompactCom 30 EtherNet/IP is a communication interface that can be embedded into any industrial device or machine to enable communication with EtherNet/IP networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.

Features and benefits



Enable communication between industrial devices and EtherNet/IP networks



Anybus CompactCom 30 Module EtherNet/IP



General	
Net Width (mm)	50
Net Height (mm)	22
Net Depth (mm)	52
Net Weight (g)	25
Packed Width (mm)	8
Packed Height (mm)	3
Packed Depth (mm)	7
Packed Weight (g)	40
Operating Temperature °C Min	-40
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	A
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8-bit parallel (30 ns access) UART (max 625kbps)
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M30 module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1



Anybus CompactCom 30 Module EtherNet/IP



Identification and Status	
Product ID	AB6214-B
Successor	AB6604-D
Country of Origin	Lithuania
HS Code	8517620000
Export Control Classification Number (ECCN)	3A991.a.2
Supply Risk Factor ERP	Used in Volume 01
Purchasing Multiple ERP	160
Physical Features	
Connectors / Input / Output	RJ45
LED Indicators	Indicates Module Status and Network Status.
Form Factor	Brick (pluggable)
Certifications and Standards	
Protection Class IP	IP20
UL Information	E214107

