



Anybus CompactCom 30 Module CANopen

Item number: AB6218-B

The Anybus CompactCom 30 CANopen is a communication interface that can be embedded into any industrial device or machine to enable communication with CANopen networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.



Enable communication between industrial devices and CANopen networks

Features and benefits



General	
Net Width (mm)	50
Net Height (mm)	22
Net Depth (mm)	52
Net Weight (g)	25
Packed Width (mm)	7
Packed Height (mm)	3
Packed Depth (mm)	8
Packed Weight (g)	25
Operating Temperature °C Min	-40
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	A
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8-bit parallel (30 ns access) UART (max 625kbps)
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M30 module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1



Identification and Status

Product ID	AB6218-B
Successor	AB6613-C
Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	3A991.a.2
Supply Risk Factor ERP	Used in Volume 01

Physical Features

Connectors / Input / Output	D-sub
LED Indicators	Indicates Module Status and Network Status.
Form Factor	Module

Certifications and Standards

Protection Class IP	IP20
UL Information	E214107