

| | |
|--|--|
| <ul style="list-style-type: none"> ● 低总拥有成本 由于集成设计，无需购买额外的天线或配件。 ● 多方向应用 支持从任何角度连接到漫游设备，如 AGVs 或控制柜。 ● 快速启动和高确定性 理想用于连接需要快速启动和高确定性的现场级设备。 ● 支持工业以太网、TCP 和 UDP 协议 支持工业以太网、TCP 和 UDP 协议，如 BACnet/IP、PROFINET、EtherNet/IP、Modbus TCP 等。 ● 易于安装 可直接安装在机柜或机器上，或使用 Bolt Base Protector 安装套件安装在杆、墙或类似位置。 ● 网络洞察 通过命令行界面 (CLI) 提供配置和诊断功能，提供更大的控制和对网络的洞察。 | <ul style="list-style-type: none"> ● 高速、漫游、双网桥接 提供快速漫游 (IEEE 802.11r) 和高链路速度 (IEEE 802.11n)。同时支持蓝牙和无线 LAN 操作，允许在两个网络之间桥接以增强连接性。 ● 轻松访问数据 无线连接到 Anybus Bolt 并轻松访问机器或机柜。无需停止或干扰生产即可配置 PLC 或机器。 ● 一体化无线通信 一体化设计，集连接器、通信处理器和集成天线于一体。使用单根电缆即可实现以太网 PoE 供电和通信。 ● 工业级设计 由于其 IP66/67 级外壳和宽工作温度范围，可 withstand 恶劣环境。选择白色顶部的 Sunbolt 选项可提供 30% 更好的保护，防止更高的温度。 ● 易于配置 通过直观的基于网页的界面，可在几秒钟内建立无线连接。 ● 完美搭配! 完全兼容 Anybus Wireless Bridge，一款专为点对点应用设计的无线产品，使您能够实现全面的无线基础设施。 |
|--|--|

Anybus Bolt Wireless Bolt - Ethernet RJ45 PoE

Item number: AWB2031-B-10PACK

The Anybus Wireless Bolt - Ethernet RJ45 PoE connects Ethernet-based machines to wireless networks via Bluetooth®, Bluetooth Low Energy, or Wi-Fi. Designed for multi-directional applications, it's ideal for establishing wireless connections with roaming machines, such as AGVs or control cabinets from any angle. PoE support simplifies installation.

Enable wireless industrial communication via Bluetooth or Wi-Fi

Features and benefits

- ✔ **Low total cost of ownership**
Thanks to the integrated design of the antenna and communication module, there's no need for additional antenna or accessory purchases.
- ✔ **Designed for multi-directional applications**
Ideal for establishing wireless connections to roaming machines, such as AGVs, or to control cabinets from any angle.
- ✔ **Quick start up and high determinism**
Ideal for connecting field-level devices that require short start-up times and high determinism.
- ✔ **Supports Industrial Ethernet, TCP, & UDP protocols**
Communicates over Industrial Ethernet, supporting protocols such as BACnet/IP, PROFINET, EtherNet/IP, Modbus TCP, as well as all TCP and UDP-based protocols.
- ✔ **Easy to install**
Attach the Wireless Bolt directly onto cabinets or machines to look like an integrated part of the installation. Or use the Bolt Base Protector mounting kit to install it on a pole, wall, or similar.
- ✔ **Insights into your network**
The Command Line Interface (CLI) provides configuration and diagnostic capabilities, offering greater control and insight into your network.
- ✔ **High-speed, roaming, dual network bridging**
Provides fast roaming (IEEE 802.11r) and high link speeds (IEEE 802.11n). Simultaneous Bluetooth and Wireless LAN operation allows bridging between the two networks for enhanced connectivity.
- ✔ **Easy access to data**
Wirelessly connect to the Anybus Bolt and easily access the machine or cabinet. Configure the PLC or machine without halting or hindering production.
- ✔ **All-in-one wireless communication**
All-in-one package featuring a connector, communication processor, and integrated antenna in the same unit. Use a single cable for both power and communication with Power over Ethernet (PoE).
- ✔ **Industrial design**
Withstands harsh environments due to its IP66/67-rated enclosure and wide operating temperature range. Choose the white top Sunbolt option for 30% better protection against higher temperatures.
- ✔ **Easy to configure**
Establish a wireless connection in seconds thanks to the intuitive web-based interface.
- ✔ **Perfect together!**
Fully compatible with Anybus Wireless Bridge, a wireless product designed for point-to-point applications, enabling you to implement comprehensive wireless infrastructure.



Anybus Bolt Wireless Bolt - Ethernet RJ45 PoE

General

| | |
|------------------------------|-----------|
| Net Weight (g) | 1165 |
| Packed Weight (g) | 1165 |
| Operating Temperature °C Min | -40 |
| Operating Temperature °C Max | 65 |
| Storage Temperature °C Min | -40 |
| Storage Temperature °C Max | 85 |
| Power Consumption (W) | 1.7 |
| Input Voltage (V) | 19-36 |
| Power over Ethernet (PoE) | 37-57 V |
| Power Connector | 3-pole |
| Housing Materials | Plastic |
| Packaging Material | Cardboard |

Identification and Status

| | |
|---|------------------------|
| Product ID | AWB2031-B-10PACK |
| Model Code | AWB2BA |
| Country of Origin | Sweden |
| HS Code | 8517620000 |
| Export Control Classification Number (ECCN) | 5A992.c |
| Supply Risk Factor ERP | Volume not defined yet |

Physical Features

| | |
|-----------------------------|-------------------------------|
| Connectors / Input / Output | RJ45, 3-pole screw connection |
|-----------------------------|-------------------------------|



Anybus Bolt Wireless Bolt - Ethernet RJ45 PoE

Wi-Fi Features

| | |
|--------------------------------------|---|
| Operation Mode | Access Point, Client |
| RF Output Power | 18 dBm EIRP (including antenna gain 3dBi) |
| Max No. Of Connections, Access Point | 7 |
| Security | WPA2 Personal; WPA2 Enterprise |

Bluetooth Features

| | |
|------------------------|------------------------|
| Operation Mode | Access Point, Client |
| Max No. Of Connections | 7 |
| Bluetooth Version | Classic Bluetooth v2.1 |

Bluetooth Low Energy Features

| | |
|-----------------------------|--|
| Operation Mode (LE) | Access Point, Client |
| RF Output Power (LE) | 14 dBm EIRP (including max antenna gain 3 dBi) |
| Max No. Of Connections (LE) | 7 |
| Bluetooth Version (LE) | Bluetooth v4.0 |

Certifications and Standards

| | |
|---------------------|--|
| Protection Class IP | IP66, IP67 |
| Vibration and Shock | Sinosodial vibration test according to IEC 60068-2-6:2007 and with extra severities; Number of axes: 3 mutually perpendicular (X:Y:Z), Duration: 10 sweep cycles in each axes, Velocity: 1 oct/min, Mode: in operation, Frequency: 5-500 Hz, Displacement ±3.5 mm, Acceleration: 2g. Shock test according to IEC 60068-2-27:2008 and with extra severities; Wave shape: half sine, Number of shocks: ±3 in each axes, Mode: In operation, Axes ± X,Y,Z, Acceleration: 30 m/s ² , Duration: 11 ms. |
| Environment | EN 61000-6-2:2019 EN 61000-4-2:2009 EN 61000-4-3:2006 + A1:2008 + A2:2010 EN 61000-4-4:2012 EN 61000-4-5:2014 EN 61000-4-6:2014 EN 61000-6-4:2019 EN 55016-2-3:2017 EN 55032:2015 EN 301 489-1 V2.2.3 EN 301 489-17 V3.1.1 |
| WEEE Category | IT and telecommunications equipment |

