



Ixxat CANbridge NT 200

Item number: 1.01.0331.20000

The Ixxat CANbridge NT 200 is a configurable CAN to CAN bridge/router to connect different CAN systems. It offers two CAN channels and supports long-distance communication, with several message processing and multiplexing functionalities. Ideal for efficient network management and system expansion.

Intelligent CAN-to-CAN bridge

Features and benefits

- ✓ **Seamless system integration**
CANbridge NT 200 enables the simple coupling of CAN systems and thus supports the conversion of networks with different bit rates or frame formats. Offers compatibility across different devices.
- ✓ **Cost savings due to simple wiring**
Optimized topologies enable simpler wiring, resulting in less cables and cost savings at installation and maintenance.
- ✓ **Customizable actions**
Additional programming of action rules using LUA for tailored responses to specific network events.
- ✓ **Configurable security levels**
Defined access levels for configuration or firmware upload.
- ✓ **Bridge operation enables CAN system expansion**
The bridge mode enables easy message exchange between CAN systems – to setup tree or star topologies.
- ✓ **On device intelligence**
Advanced filter, ID translation, data mapping and multiplexing functionalities streamline network traffic and enhance efficiency.
- ✓ **Device and system protection**
Network segmentation with galvanic isolation protects devices against damage caused by voltage peaks.
- ✓ **Easy configuration and maintenance**
Windows configuration tool allows for easy setup and maintenance via USB.



General	
Net Width (mm)	99
Net Height (mm)	114.5
Net Depth (mm)	22.5
Net Weight (g)	250
Packed Width (mm)	13
Packed Height (mm)	5
Packed Depth (mm)	17
Packed Weight (g)	270
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	10 to 95 %, non-condensing
Current Consumption Type Value at Vcc Nom (mA)	110 mA (24 V DC), 220 mA (12 V DC)
Input Voltage (V)	9 V to 36 V DC, with overvoltage and polarity protection
Isolation	1 kV DC for 1 sec.
Configuration	The Ixxat CANbridge NT series is configured and updated with a straightforward Windows configuration tool through USB. This tool simplifies setting up filters, mapping, multiplexers, or translation rules, requiring no programming expertise.
Content of Delivery	CANbridge NT device, user manual, Mini USB cable, available as free download: CAN-Gateway Configurator tool, CAN driver VCI, simple CAN monitor "canAnalyser Mini"
Not Included (in delivery)	comprehensive and powerful driver and software packages are available as free download



General

Mounting	DIN rail mount (bracket included)
Housing Materials	Polyamide housing for top hat rail mounting
Packaging Material	Cardboard
Warranty (years)	1

Identification and Status

Product ID	1.01.0331.20000
Country of Origin	Germany
HS Code	8517620000
Export Control Classification Number (ECCN)	EAR99
Supply Risk Factor ERP	Used in Volume 01
Purchasing Multiple ERP	104

Physical Features

Connectors / Input / Output	1 x Mini USB port, 3 x screw terminals (2 x fieldbus, 1 x power)
------------------------------------	--

CAN Features

CAN Mode	CAN high-speed (ISO 11898-2:2016)
CAN Baud Rate	5 kBit/s to 1 MBit/s

Certifications and Standards

Protection Class IP	IP20
ETIM Classification	EC000673
WEEE Category	IT and telecommunications equipment