



Anybus ProfiHub A5

Item number: 16010

The Anybus A5 is designed for simple network segmentation in harsher environments with its IP 65 classification

A weather resistant 4 channel repeater



Features and benefits

✓ **Reliable communication**

The A5 complies with the strict rules of spur lines and star networks

✓ **Compatible with different application speeds**

The repeater is transparent and handles a connection speed from 9.6Kbps to 12Mbps easily

✓ **Isolated channels**

The 5 isolated channels are designed to handle up to 31 devices and a length equal to the main bus

Anybus ProfiHub A5



General

Net Width (mm)	213
Net Height (mm)	210
Net Depth (mm)	95
Net Weight (g)	1239
Packed Width (mm)	13
Packed Height (mm)	23
Packed Depth (mm)	31
Packed Weight (g)	1239
Operating Temperature °C Min	-40
Operating Temperature °C Max	75
Current Consumption Type Value at Vcc Nom (mA)	130 mA
Current Consumption Max value at Vcc nom (mA)	130 mA
Input Voltage (V)	10...32 VDC
Power Wire Diameter (mm)	< 2.5 mm ²
Warranty (years)	1 Year

Identification and Status

Product ID	16010
Country of Origin	Netherlands (the)
HS Code	8471800000
Export Control Classification Number (ECCN)	EAR99

Anybus ProfiHub A5



Identification and Status

Supply Risk Factor ERP	Volume not defined yet
Purchasing Multiple ERP	1

Certifications and Standards

Protection Class IP	IP65
WEEE Category	IT and telecommunications equipment