

Angular Angula

Anybus ProfiHub B2+

Item number: 17210R

For PROFIBUS network designs, the ProfiHub B2+ offers a reliable and robust backbone solution with robust message checking and selectable redundancy on communication and power supply.

Efficient network segmentation with integrated diagnostics down to the last device

Features and benefits

Diagnostics slave device
 Capability to show diagnostic messages down to the last device with ComBricks

Compatible with different application speeds
The repeater is transparent and handles a connection speed from 9.6Kbps to 12Mbps easily

Network segmentation

Increase network reliability by creating isolated segmentations



Anybus ProfiHub B2+

Export Control Classification

Number (ECCN)

EAR99



General	
Net Width (mm)	111
Net Height (mm)	102
Net Depth (mm)	32
Net Weight (g)	660
Packed Width (mm)	16
Packed Height (mm)	6
Packed Depth (mm)	26
Packed Weight (g)	660
Operating Temperature °C Min	-25
Operating Temperature °C Max	70
Current Consumption Type Value at Vcc Nom (mA)	125 mA
Current Consumption Max value at Vcc nom (mA)	125 mA
Input Voltage (V)	931
Power Wire Diameter (mm)	< 2.5 mm ²
Warranty (years)	1 Year
Identification and Status	
Product ID	17210R
Country of Origin	Netherlands (the)
HS Code	8471800000



Anybus ProfiHub B2+



Identification and Status

Supply Risk Factor ERP Volume not defined yet

Certifications and Standards

Protection Class IP	IP20
WEEE Category	IT and telecommunications equipment

