

Anybus ProfiHub B2FOR+ (Multi-Mode)

Item number: 17230

The ProfiHub B2FOR+ is a cost-effective solution to link PROFIBUS fiber optic to multiple RS 485 segments and vice versa allowing ring topologies.



Redundant network expansion over long distances

Features and benefits

- One fiber opitc channel, divided into 2 ports

 Allowing creation for additional redundancy on the ring
- Ring redundancy
 Strenghten the backbone of your network by creating additional redundancy via a ring topology
- 2 galvanically isoltated channels

 Avoid daisy chained network interruptions







General	
Net Width (mm)	111
Net Height (mm)	102
Net Depth (mm)	40
Net Weight (g)	591
Packed Width (mm)	16
Packed Height (mm)	6
Packed Depth (mm)	26
Packed Weight (g)	591
Operating Temperature °C Min	-25
Operating Temperature °C Max	70
Current Consumption Type Value at Vcc Nom (mA)	250 mA
Current Consumption Max value at Vcc nom (mA)	250 mA
Input Voltage (V)	931 VDC
Power Wire Diameter (mm)	< 2.5 mm ²
Warranty (years)	1 Year

Identification and Status	
Product ID	17230
Country of Origin	Netherlands (the)
HS Code	8471800000
Export Control Classification Number (ECCN)	EAR99







Identification and Status	
Supply Risk Factor ERP	Volume not defined yet
Purchasing Multiple ERP	1
Certifications and Standards	
Protection Class IP	IP20
WEEE Category	IT and telecommunications equipment

