



Anybus ComBricks PA Link/Coupler

Item number: 101-201610

The Anybus PROFIBUS PA link/coupler module enables seamless high speed integration to PROFIBUS PA.



Easy integration of PROFIBUS PA into your existing DP installation

Features and benefits

✓ **Integrated oscilloscope**

The combined internal ProfiTrace and oscilloscope make this product extremely useful for remote maintenance over Ethernet. Jitter, noise, DC current, DC voltage, bar graph and oscilloscope, it is all there and easy to access.

✓ **Easy switch over**

This product can directly replace 3rd party Non-Ex PA couplers/links and can be used as a monitor behind existing 3rd party Non-Ex PA couplers.

✓ **PA PROFIBUS extension made easy**

ComBricks is able to carry 9 PA links and a RS 485 or Fiber Optic module. It can also be a customized mix of PA modules with other communication modules.



Anybus ComBricks PA Link/Coupler

General	
Net Weight (g)	170
Packed Width (mm)	6
Packed Height (mm)	14
Packed Depth (mm)	20
Packed Weight (g)	272
Operating Temperature °C Min	-20
Operating Temperature °C Max	60
Current Consumption Type Value at Vcc Nom (mA)	350 mA
Current Consumption Max value at Vcc nom (mA)	550 mA
Power Wire Diameter (mm)	< 2.5 mm ²
Mounting	DIN rail mount (bracket included)
Housing Materials	Plastic
Packaging Material	Cardboard
Warranty (years)	1 Year

Identification and Status	
Product ID	101-201610
Country of Origin	Netherlands (the)
HS Code	8471800000
Export Control Classification Number (ECCN)	EAR99
Supply Risk Factor ERP	Volume not defined yet



Anybus ComBricks PA Link/Coupler

Identification and Status

Purchasing Multiple ERP	1
-------------------------	---

Certifications and Standards

Protection Class IP	IP20
---------------------	------

WEEE Category	IT and telecommunications equipment
---------------	-------------------------------------