

Anybus ProfiHub A5 (110V or 230V)

Item number: 16013

The Anybus A5 is designed for simple network segmentation in harsher environments with its IP 65 classification



A weather resistant 4 channel repeater

Features and benefits

Reliable communication

The A5 complies with the strict rules of spur lines and star networks

Integrated power supply

This unit is equipped with an integrated 110-230VAC power supply to be installed easily

✓ Isolated channels

The 5 isolated channels are designed to handle up to 31 devices and a length equal to the main bus







General	
Net Width (mm)	213
Net Height (mm)	210
Net Depth (mm)	95
Net Weight (g)	1313
Packed Width (mm)	13
Packed Height (mm)	23
Packed Depth (mm)	31
Packed Weight (g)	1313
Operating Temperature °C Min	-40
Operating Temperature °C Max	75
Power Wire Diameter (mm)	< 2.5 mm ²
Warranty (years)	1 Year

	TUETTUTTUTT ATTU STATUS	
	Product ID	16013
	Country of Origin	Netherlands (the)
	HS Code	8471800000
	Export Control Classification Number (ECCN)	EAR99
	Supply Risk Factor FRP	Volume not defined vet

$\bigcap \bigcirc \lor + if$	ication	a	C + a = a	arda
	11 '21 11 11 1	ς and	$>$ 1 \approx 1 \times 1	AHIS
	ioation	o ana	utana	uluu

1

Protection Class	IP	IP65

Purchasing Multiple ERP







Certifications and Standards

WEEE Category

IT and telecommunications equipment

