



## Anybus T1 Terminator

Item number: 101-00211A

The T1 Terminator provides active termination for PROFIBUS segments which are based on RS 485.

Manage & Reduce Termination faults on PROFIBUS DP RS-485

## Features and benefits

Active termination supporting all PROFIBUS RS 485 protocols

390 / 220 / 390 Ohm compatible with all baud rates (9.6kbps -12Mbps)

Redundant power supply with indicator LEDs

Two power connectors with status LED indication on availability of each power supply. Power auto take over without a delay when losing a power supply.

Screw Terminal Port & DB9 Port

Screw terminal port for PROFIBUS DP segment and additional DB9 port for measuring the signal with diagnostic tools like ProfiTrace







General	
Net Width (mm)	55
Net Height (mm)	106
Net Depth (mm)	33
Net Weight (g)	120
Packed Width (mm)	8
Packed Height (mm)	6
Packed Depth (mm)	11
Packed Weight (g)	175
Operating Temperature °C Min	-20
Operating Temperature °C Max	60
Current Consumption Type Value at Vcc Nom (mA)	65 mA
Current Consumption Max value at Vcc nom (mA)	65 mA
Input Voltage (V)	1928 VDC
Power Wire Diameter (mm)	<2.5 mm²
Warranty (years)	1 Year

Identification and Status	
Product ID	101-00211A
Country of Origin	Netherlands (the)
HS Code	8471800000
Export Control Classification Number (ECCN)	EAR99



## Anybus T1 Terminator



Identification and Status	
Supply Risk Factor ERP	Volume not defined yet
Purchasing Multiple ERP	1
Certifications and Standards	
Protection Class IP	IP20
WEEE Category	IT and telecommunications equipment

