

## Anybus Defender 6004 - DPI/FW

Item number: ABD6004-DPIFW

Advanced industrial security appliance engineered to provide unparalleled protection for operational technology (OT) networks. Featuring a robust combination of NAT, Routing as well as Deep Packet Inspection (DPI) on common industrial protocols and Intrusion Detection it serves as a cornerstone for safeguarding both manufacturing and critical infrastructure against a myriad of cyberthreats.



*Industrial Security Appliance with Industrial Protocol  
Screening and Asset Access Control*

### Features and benefits

- ✓ **Interfaces**  
Rugged Fan-less IP50 construction for tough environments with 1x WAN and 3x LAN Gigabit Ethernet ports for 4 physical segments with VLAN support for many more logical segments.
- ✓ **Intrusion Protection System (IPS)**  
Virtual Patching with integrated Snort and Suricata Intrusion Detection & Protection Systems. Customisable signatures.
- ✓ **Rich Network Security Controls**  
Simplified NAT Configuration facilitates the setup for single or multiple IP addresses, subnets, or transparent layer 2 firewalling, capable of bridging interfaces and filtering traffic.
- ✓ **Central Management**  
Optional Central Anybus Cybersecurity Console for management of a group of Defenders.
- ✓ **Deep Packet Inspection (DPI)**  
Anybus Defender supports popular industry standard protocols and can auto-learn industrial network traffic to minimize manual rule creation.
- ✓ **Graphical User Interface (GUI)**  
Configuration via on board Web interface with use-case wizards for easy configuration. Create rules effortlessly with One-Click Easy Rule creation directly from firewall logs, alongside Floating Rules applicable across all interfaces.
- ✓ **Asset Discovery & Inventory**  
Network asset identification scanner supporting various industrial specific protocols and methods to discovery, query and investigate asset. Provides connected assets make, type, version and patch level details – with accuracy score.

# Anybus Defender 6004 - DPI/FW



## General

Net Weight (g)	1270
Operating Temperature °C Min	0
Operating Temperature °C Max	50
Current Consumption Max value at Vcc nom (mA)	1100mA
Power Consumption (W)	26.4W
Input Voltage (V)	24VDC
Warranty (years)	3

## Identification and Status

Product ID	ABD6004-DPIFW
Country of Origin	United States of America (the)
HS Code	8517620000
Export Control Classification Number (ECCN)	5A992.c

## Certifications and Standards

Protection Class IP	IP50
---------------------	------