

Item number: INMBSACA001I000

The Bosch-Modbus interface allows full bidirectional communication between Bosch Commercial and VRF systems and Modbus RTU (RS-485) networks. The interface acts as a server device for the installation, accessing all signals from the air conditioner unit.



Bosch to Modbus - 1 indoor unit

Features and benefits

- Modbus RTU (EIA-485) server device

 The interface acts as a Modbus server device through its Modbus RTU (EIA-485 connector) port.
- Energy savings through a window contact function

 This function helps minimize costs, as HVAC systems are a major building energy consumer.
- AC unit control by both the remote and Modbus RTU

 The AC unit can be simultaneously controlled by the manufacturer's remote controller and Modbus RTU.
- **Dual configuration options**

Configuration is carried out through the interface's onboard DIP switches and the Modbus interface.

- Total unit control and monitoring from Modbus RTU

 Through internal variables, running hours counter (for maintenance purposes), and error indication.
- Multiple mounting options

Mounting options include DIN rail, wall, or, in some AC models, even inside the indoor unit.





General	
Net Width (mm)	53
Net Height (mm)	58
Net Depth (mm)	93
Net Weight (g)	90
Operating Temperature °C Min	0
Operating Temperature °C Max	60
Input Voltage (V)	From the AC unit.
Power Connector	Other
Capacity	1 indoor unit.
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
Content of Delivery	Intesis Gateway, Installation Manual, AC Connection cable.
Mounting	DIN rail mount (bracket included), Wall mount
Housing Materials	Plastic
Warranty (years)	3 years
Packaging Material	Cardboard
Identification and Status	
Product ID	INMBSACA001I000
Country of Origin	Spain





8517620000

EAR99

HS Code

Number (ECCN)

Export Control Classification



Identification and Status	
Supply Risk Factor ERP	Volume not defined yet
Purchasing Multiple ERP	1
Physical Features	
Connectors / Input / Output	Power supply, EIA-485, Ethernet.
DIP & Rotary Switches	EIA-485 serial port configuration.
Certifications and Standards	
ETIM Classification	EC001604
WEEE Category	IT and telecommunications equipment





Use Case



Integration example.

