

## Panasonic ECOi and PACi systems to Modbus RTU Interface

Item number: INMBSPAN001R000

The Panasonic-Modbus interface allows full bidirectional communication between Panasonic ECOi and PACi air conditioner units and Modbus RTU (RS-485) networks. The interface acts as a server device for the installation, accessing all signals from the air conditioner unit. A wired remote controller can also be part of the network.



*Panasonic to Modbus RTU - 1 indoor unit*

### Features and benefits

- ✓ **Modbus RTU (EIA-485) server device**  
The interface acts as a Modbus server device through its Modbus RTU (EIA-485 connector) port.
- ✓ **Energy savings through a window contact function**  
This function helps minimize costs, as HVAC systems are a major building energy consumer.
- ✓ **AC unit control by both the remote and Modbus RTU**  
The AC unit can be simultaneously controlled by the manufacturer's remote controller and Modbus RTU.
- ✓ **Multiple mounting options**  
Mounting options include DIN rail, wall, or, in some AC models, even inside the indoor unit.
- ✓ **Dual configuration options**  
Configuration is carried out through the interface's onboard DIP switches and the Modbus interface.
- ✓ **Total unit control and monitoring from Modbus RTU**  
Through internal variables, running hours counter (for maintenance purposes), and error indication.
- ✓ **No external power required**  
The interface is powered directly from the AC unit, so no external power supply is required.

# Panasonic ECOi and PACi systems to Modbus RTU Interface



General	
Net Width (mm)	53
Net Height (mm)	58
Net Depth (mm)	93
Net Weight (g)	95
Operating Temperature °C Min	0
Operating Temperature °C Max	60
Input Voltage (V)	From the AC unit.
Power Connector	Other
Capacity	1 indoor unit.
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
Content of Delivery	Intesis gateway and installation manual.
Mounting	DIN rail mount (bracket included), Wall mount
Housing Materials	Plastic
Warranty (years)	3 years
Packaging Material	Cardboard

Identification and Status	
Product ID	INMBSPAN001R000
Country of Origin	Spain
HS Code	8517620000
Export Control Classification Number (ECCN)	EAR99

# Panasonic ECOi and PACi systems to Modbus RTU Interface



## Identification and Status

Supply Risk Factor ERP	Volume not defined yet
Purchasing Multiple ERP	1

## Physical Features

Connectors / Input / Output	EIA-485, AC port.
DIP & Rotary Switches	EIA-485 serial port configuration.

## Certifications and Standards


ETIM Classification	EC001604
WEEE Category	IT and telecommunications equipment



## Use Case

**Panasonic**

**Modbus**



Integration example.