

Anybus CompactCom 30 Module EtherNet/IP Beacon - 2 port without housing



Item number: AB6328-B

The Anybus CompactCom 30 EtherNet/IP Beacon 2 port without housing is a communication interface that can be embedded into any industrial device or machine to enable communication with EtherNet/IP Beacon networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.

Enable communication between industrial devices and EtherNet/IP Beacon networks

Features and benefits

Anybus CompactCom 30 Module EtherNet/IP Beacon - 2 port without housing



General	
Net Width (mm)	37
Net Height (mm)	16
Net Depth (mm)	51
Net Weight (g)	18
Packed Weight (g)	18
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	B
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8-bit parallel (30 ns access) UART (max 625kbps)
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M30 module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1

Identification and Status	
Product ID	AB6328-B
Successor	AB6704-D
Country of Origin	Sweden

Anybus CompactCom 30 Module EtherNet/IP Beacon - 2 port without housing



Identification and Status

HS Code	8517620000
Export Control Classification Number (ECCN)	3A991.a.2
Supply Risk Factor ERP	Volume not defined yet

Physical Features

Connectors / Input / Output	2x RJ45
LED Indicators	Indicates Module Status, Network Status and Link/Activity.
Form Factor	Module without Housing

Certifications and Standards

Protection Class IP	IP20
UL Information	E214107

Anybus CompactCom 30 Module EtherNet/IP Beacon - 2 port without housing



Use Case

