

## Anybus CompactCom 30 Module PROFINET IO without housing

Item number: AB6315-B

The Anybus CompactCom 30 PROFINET IO without housing is a communication interface that can be embedded into any industrial device or machine to enable communication with PROFINET IO networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.



*Enable communication between industrial devices and  
PROFINET IO networks*

### Features and benefits

# Anybus CompactCom 30 Module PROFINET IO without housing



## General

Net Width (mm)	37
Net Height (mm)	16
Net Depth (mm)	51
Net Weight (g)	15
Packed Weight (g)	15
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	A
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8-bit parallel (30 ns access) UART (max 625kbps)
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M30 module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1

## Identification and Status

Product ID	AB6315-B
Successor	AB6705-D
Country of Origin	Sweden

# Anybus CompactCom 30 Module PROFINET IO without housing



## Identification and Status

HS Code	8517620000
Export Control Classification Number (ECCN)	3A991.a.2
Supply Risk Factor ERP	Used in Volume 01

## Physical Features

Connectors / Input / Output	RJ45
LED Indicators	Indicates Module Status, Network Status and Link/Activity.
Form Factor	Module without Housing

## Certifications and Standards

Protection Class IP	IP20
UL Information	E214107



## Use Case

