



Anybus CompactCom 30 Module CANopen

Item number: AB6218-B

The Anybus CompactCom 30 CANopen is a communication interface that can be embedded into any industrial device or machine to enable communication with CANopen networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.



Enable communication between industrial devices and CANopen networks

Features and benefits



Identification and Status

| | |
|---|------------|
| Product ID | AB6218-B |
| Successor | AB6613-C |
| Country of Origin | Sweden |
| HS Code | 8517620000 |
| Export Control Classification Number (ECCN) | 3A991.a.2 |

General

| | |
|---|-----------------------|
| Net Width (mm) | 50 |
| Net Height (mm) | 22 |
| Net Depth (mm) | 52 |
| Net Weight (g) | 25 |
| Packed Width (mm) | 7 |
| Packed Height (mm) | 3 |
| Packed Depth (mm) | 8 |
| Packed Weight (g) | 25 |
| Operating Temperature °C Min | -40 |
| Operating Temperature °C Max | 70 |
| Storage Temperature °C Min | -40 |
| Storage Temperature °C Max | 85 |
| Current Consumption Class (CompactCom series) | A |
| Input Voltage (V) | 3.3 VDC, +/- 0.15 VDC |



General

| | |
|------------------------------|--|
| Application Interface | 8-bit parallel (30 ns access) UART (max 625kbps) |
| Isolation | Galvanic Isolation |
| Content of Delivery | CompactCom M30 module |
| Mounting | PCB mounting via a customized CompactFlash connector |
| Warranty (years) | 1 |

Physical Features

| | |
|------------------------------------|---|
| Connectors / Input / Output | D-sub |
| LED Indicators | Indicates Module Status and Network Status. |
| Form Factor | Module |

Certifications and Standards

| | |
|----------------------------|---------|
| Protection Class IP | IP20 |
| UL Information | E214107 |