

Anybus CompactCom 30 Module USB without housing

Item number: AB6309-B

The Anybus CompactCom 30 USB without housing is a passive module that acts as a physical layer converter for USB communication. As a passive module, it doesn't process the serial bitstream. This module enables a transparent USB channel using the Anybus CompactCom slot. The module uses the serial channel of the application interface.



Enables transparent USB communication

Features and benefits



Anybus CompactCom 30 Module USB without housing



Identification and Status	
Product ID	AB6309-B
Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	3A991.a.2
General	
Net Width (mm)	37
Net Height (mm)	16
Net Depth (mm)	51
Net Weight (g)	18
Packed Weight (g)	18
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	A
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	RxD/TxD
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M30 Passive module
Mounting	PCB mounting via a customized CompactFlash connector



Anybus CompactCom 30 Module USB without housing



General	
Warranty (years)	1
Physical Features	
Connectors / Input / Output	USB
LED Indicators	Power
Form Factor	Module without Housing
Certifications and Standards	
Protection Class IP	IP20
UL Information	E214107

