

Fujitsu RAC and VRF systems to Modbus RTU Interface (to CN connector)

Item number: IN485FGL001I000

The Fujitsu-Modbus interface allows full bidirectional communication between Fujitsu RAC and VRF systems and Modbus RTU (RS-485) networks. The interface acts as a server device for the installation, accessing all signals from the air conditioner unit.



Fujitsu to Modbus RTU - 1 indoor unit

Features and benefits

- ✓ **BACnet MS/TP and Modbus RTU supported**
The interface supports both BACnet MS/TP and Modbus RTU protocols.
- ✓ **Energy savings through a window contact function**
This function helps minimize costs, as HVAC systems are a major building energy consumer.
- ✓ **Wide AC unit control and monitoring from Modbus**
Wide AC unit control and monitoring from Modbus, including EcoMode, filter alarm, errors, and more.
- ✓ **No external power required**
The interface is powered directly from the AC unit, so no external power supply is required.
- ✓ **Dual configuration options**
Configuration is carried out through the interface's onboard DIP switches and the Modbus interface.
- ✓ **Total unit control and monitoring from Modbus RTU**
Through internal variables, running hours counter (for maintenance purposes), and error indication.
- ✓ **AC unit control by both the remote and Modbus RTU**
The AC unit can be simultaneously controlled by the manufacturer's remote controller and Modbus RTU.
- ✓ **Multiple mounting options**
Mounting options include DIN rail, wall, or, in some AC models, even inside the indoor unit.

Fujitsu RAC and VRF systems to Modbus RTU Interface (to CN connector)



Identification and Status

Product ID	IN485FGL001I000_MBS_FGL
Country of Origin	Spain
Export Control Classification Number (ECCN) ERP	8517620000
HS Code	8517620000
Export Control Classification Number (ECCN)	EAR99

General

Net Width (mm)	53
Net Height (mm)	58
Net Depth (mm)	93
Net Weight (g)	180
Operating Temperature °C Min	0
Operating Temperature °C Max	70
Input Voltage (V)	From the AC unit.
Power Connector	Other
Capacity	1 indoor unit.
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
Content of Delivery	Intesis Gateway, Installation Manual, AC Connection cable.
Mounting	DIN rail mount (bracket included), Wall mount
Housing Materials	Plastic
Warranty (years)	3 years

Fujitsu RAC and VRF systems to Modbus RTU Interface (to CN connector)



General

Packaging Material	Cardboard
--------------------	-----------

Physical Features

Connectors / Input / Output	EIA-485, HVAC port.
LED Indicators	AC and network status.
DIP & Rotary Switches	EIA-485 serial port configuration.

Certifications and Standards

ETIM Classification	EC001604
UNSPSC	ERPREADY
WEEE Category	IT and telecommunications equipment

Fujitsu RAC and VRF systems to Modbus RTU Interface (to CN connector)



Use Case

