



Anybus ComBricks Head Station 1A

Item number: 101-20011A

The Head Station is the primary element of ComBricks and has to be inserted in the most left slot of the fixed backplane socket. It schedules the interaction between all modules and provides data storage and an Ethernet interface for the user.



The primary element of the ComBricks modular system

Features and benefits

- ✓ **The main power source for all**
The Head Station provides power to all modules through its redundant power supply.
- ✓ **Remote web server access**
Have full data insight into your network measurements such as status of all devices, live lists, statistics, message recordings, PROFIBUS events and more whenever you need it.
- ✓ **Supporting multiple networks**
Repeater modules can be set to 4 networks.



Anybus ComBricks Head Station 1A

General

Net Weight (g)	147
Packed Width (mm)	10
Packed Height (mm)	15
Packed Depth (mm)	20
Packed Weight (g)	397
Operating Temperature °C Min	-20
Operating Temperature °C Max	60
Current Consumption Type Value at Vcc Nom (mA)	73 mA
Current Consumption Max value at Vcc nom (mA)	800 mA
Input Voltage (V)	11...26 VDC
Power Wire Diameter (mm)	< 2.5 mm ²
Mounting	DIN rail mount (bracket included)
Housing Materials	Plastic
Packaging Material	Cardboard
Warranty (years)	1 Year

Identification and Status

Product ID	101-20011A
Country of Origin	Netherlands (the)
HS Code	8471800000
Export Control Classification Number (ECCN)	EAR99



Anybus ComBricks Head Station 1A

Certifications and Standards

Protection Class IP	IP20
WEEE Category	IT and telecommunications equipment