


## Anybus ProfiHub B4FOR+ (Single-Mode)

Item number: 17440

The ProfiHub B4FOR+ is a cost-effective solution to link PROFIBUS fiber optic to multiple RS 485 segments and vice versa allowing ring topologies.



Redundant network expansion over long distances

#### Features and benefits

- One fiber opitc channel, divided into 2 ports

  Allowing creation for additional redundancy on the ring
- Ring redundancy
  Strenghten the backbone of your network by creating additional redundancy via a ring topology
- 4 galvanically isoltated channels
  Avoid daisy chained network interruptions





### Anybus ProfiHub B4FOR+ (Single-Mode)

General	
Net Width (mm)	111
Net Height (mm)	167
Net Depth (mm)	40
Net Weight (g)	724
Packed Width (mm)	13
Packed Height (mm)	20
Packed Depth (mm)	24
Packed Weight (g)	814
Operating Temperature °C Min	-25
Operating Temperature °C Max	70
Current Consumption Type Value at Vcc Nom (mA)	250 mA
Current Consumption Max value at Vcc nom (mA)	250 mA
Input Voltage (V)	931 VDC
Power Wire Diameter (mm)	< 2.5 mm <sup>2</sup>
Warranty (years)	1 Year

#### 







# Certifications and Standards Protection Class IP IP20 WEEE Category IT and telecommunications equipment

