

Ewon Flexy extension card - 4G APAC

Item number: FLB3209_00

This card boosts Ewon Flexy's connectivity with a 4G LTE modem for APAC region. Ideal for field applications lacking wired internet. Requires only a SIM card with data plan for Talk2m cloud. Safe VPN connectivity for SCADA applications without the hassle of provisioning a fixed IP address. Compatible with Ewon Flexy 10x, 20x series and 205.



Interchangeable extension card for enhanced connectivity

Features and benefits

✓ **Build your own Flexy gateway**

Keep up with the evolution of communication technologies while protecting your investment in the device! The Ewon Flexy extension cards make this gateway highly modular and flexible.

Ewon Flexy extension card - 4G APAC



Identification and Status

Product ID	FLB3209_00
Model Code	03501
Predecessor	FLB3202_01
Country of Origin	Belgium
HS Code	8517790000
Export Control Classification Number (ECCN)	5A992.c

General

Net Width (mm)	22
Net Height (mm)	79
Net Depth (mm)	82
Net Weight (g)	47.5
Packed Width (mm)	102
Packed Height (mm)	30
Packed Depth (mm)	95
Packed Weight (g)	69
Operating Temperature °C Min	-25
Operating Temperature °C Max	+60
Storage Temperature °C Min	-30
Storage Temperature °C Max	+70
Content of Delivery	This product consists of the following components: an electronic extension board inserted in a plastic front plate and packed in an ESD plastic bag sealed with a yellow sticker, legal references in paper version and a cardboard box.

Ewon Flexy extension card - 4G APAC



General

Not Included (in delivery)	Antenna
Housing Materials	Plastic
Packaging Material	Cardboard
Warranty (years)	5

Physical Features

Connectors / Input / Output	1x Antenna connector: SMA-F Female
------------------------------------	------------------------------------

Wireless Features

Antenna Connector	SMA
Antenna	Not Included
Cellular Standards	Our Modem Flexy Extension Cards FLB3208, FLB320A, FLB3209, FLB3271 are only supported if the Flexy Base Unit runs the firmware version 14.8s0 and higher.
Frequencies & Bands	4G: B1, B3, B5, B7, B8, B18, B19, B21, B28, B38,B39, B40,B41 3G: B1, B5, B6, B8, B9, B19

Certifications and Standards

Environment	Temperature - Operating & Storage tested according to: IEC 60068-2-1 Cold test, IEC 60068-2-2 Dry heat test, IEC 60068-2-14 Change of temperature, IEC 60068-2-30 Cyclic damp heat test
Vibration and Shock	Vibration & shocks tested according to: IEC 60068-2-27 Bumps, IEC 60068-2-64 Vibration (broad-band random), IEC 60068-2-6 Vibration (sinusoidal)
WEEE Category	IT and telecommunications equipment
Other Certification	Giteki Japan, Malaysia, Thailand