

Anybus ProfiHub A5

Item number: 16010

The Anybus A5 is designed for simple network segmentation in harsher environments with its IP 65 classification



A weather resistant 4 channel repeater

Features and benefits

Reliable communication

The A5 complies with the strict rules of spur lines and star networks

Compatible with different application speeds

The repeater is transparent and handles a connection speed from 9.6Kbps to 12Mbps easily

Isolated channels

The 5 isolated channels are designed to handle up to 31 devices and a length equal to the main bus



Anybus ProfiHub A5



Identification and Status	
Product ID	16010
Country of Origin	Netherlands (the)
HS Code	8471800000
Export Control Classification Number (ECCN)	EAR99
General	
Net Width (mm)	213
Net Height (mm)	210
Net Depth (mm)	95
Net Weight (g)	1239
Packed Width (mm)	13
Packed Height (mm)	23
Packed Depth (mm)	31
Packed Weight (g)	1239
Operating Temperature °C Min	-40
Operating Temperature °C Max	75
Current Consumption Type Value at Vcc Nom (mA)	130 mA
Current Consumption Max value at Vcc nom (mA)	130 mA
Input Voltage (V)	1032 VDC
Power Wire Diameter (mm)	< 2.5 mm²
Warranty (years)	1 Year



Anybus ProfiHub A5



Certifications and Standards Protection Class IP IP65 WEEE Category IT and telecommunications equipment

