

Anybus EtherNet/IP Linking Devices – EtherNet/IP to Serial Linking Device

Item number: HMS-EN2SE-R

The Anybus EtherNet/IP to Serial Linking Device converts serial to EtherNet/IP, enabling you to connect any serial device to a Logix PLC control system. The linking device presents serial data as easily processed I/O data, offloading the PLC from working with extra calculations and allowing for seamless integration with Studio 5000.



Enable seamless integration of serial devices to Studio 5000

Features and benefits

- ✓ **Seamless integration with Studio 5000**
The unique Studio 5000[®] Logix designer integration provides access to everything, including serial network configuration. No need for extra 3rd-party software, licenses, or programming.
- ✓ **Connect, configure, done**
EtherNet/IP Linking Devices are configured using a Custom Add-On Profile in Studio 5000, dynamically generating data structures for each device and eliminating the need for ladder logic files.
- ✓ **3-year warranty**
The linking devices are designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✓ **Increased performance - Logix PLC**
Presents serial data as easily processed I/O data offloading the Logix PLC from extra calculations.
- ✓ **Life cycle management**
HMS maintains every part of the Linking Devices, including network updates, throughout the product's lifecycle.
- ✓ **Convert any type of serial protocol**
The Linking Device can convert any standard serial protocol such as Modbus RTU, DF1, or any other Request/Response or Produce/Consume proprietary protocol.
- ✓ **Automatic tag names**
Our Custom Add-On Profile for Studio 5000 supports the automatic generation of named and structured controller tags, eliminating the need to create alias tags.
- ✓ **No programming required**
Easy to set up with the Custom Add-On Profile. No programming required!
- ✓ **Trusted partner**
Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.

Anybus EtherNet/IP Linking Devices – EtherNet/IP to Serial Linking Device



Identification and Status

Product ID	HMS-EN2SE-R
Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	5A991.b.1

General

Net Width (mm)	27
Net Height (mm)	120
Net Depth (mm)	75
Net Weight (g)	155
Packed Width (mm)	14
Packed Height (mm)	6
Packed Depth (mm)	17
Packed Weight (g)	320
Operating Temperature °C Min	0
Operating Temperature °C Max	55
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	0-95% non condensing
Current Consumption Type Value at Vcc Nom (mA)	100mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	300mA @ 24V DC

Anybus EtherNet/IP Linking Devices – EtherNet/IP to Serial Linking Device



General

Input Voltage (V)	24V DC (-10% to +10%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Isolation	TRUE
Maximum Installation Altitude (m)	up to 2 000 m
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	PC ABS, UL 94
Packaging Material	Cardboard

Physical Features

Connectors / Input / Output	1x D-sub 9-pin female, 2xRJ45
------------------------------------	-------------------------------

EtherNet/IP Features

EtherNet/IP Mode	Adapter / Slave
EtherNet/IP Supported Functionality	Preinstalled Add On Profile in Studio 5000 Logix Designer; Daisy Chaining
EtherNet/IP Configuration File	EDS available
EtherNet/IP Bandwidth	10/100MBit
EtherNet/IP Input Data Size	509 bytes
EtherNet/IP Output Data Size	505 bytes

Modbus-RTU Features

Modbus-RTU Mode	Client / Master
Modbus-RTU Supported Functionality	RS-232; RS-422; RS485; DF1; Standard Modbus RTU Master; Custom Request / Responce commands; Custom Produce / Consume transactions; Trigger initiated transactions 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze
Modbus-RTU Functions Supported	1, 2, 3, 4, 5, 6, 7, 8, 11, 12, 15, 16, 17, 20, 21, 22, 24
Modbus-RTU Baud Rate	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600 bit/s
Modbus-RTU Input Data Size	512 bytes

Anybus EtherNet/IP Linking Devices – EtherNet/IP to Serial Linking Device



Modbus-RTU Features

Modbus-RTU Output Data Size	512 bytes
------------------------------------	-----------

Serial Features

Connector	1x D-sub 9-pin female
Max Nodes	31
Baud Rate	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600 bit/s
Supported Functionality	RS-232; RS-422; RS485; DF1; Standard Modbus RTU Master; Custom Request / Responce commands; Custom Produce / Consume transactions; Trigger initiated transactions 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze

Certifications and Standards

Protection Class IP	IP20
Recycle / Disposal	TRUE
UL Information	E214107: Ord.Loc UL508, CSA C22.2 No. 14-10; E203225: Haz.Loc CL I DIV2 GP A,B,C,D, ANSI/ISA 12.12.01, CSA C22.2 No. 213
Environment	EN 50082-2, EN 55011, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment