

## Anybus CompactCom 30 Module CANopen without housing



**Item number: AB6318-B**

The Anybus CompactCom 30 CANopen without housing is a communication interface that can be embedded into any industrial device or machine to enable communication with CANopen networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.

*Enable communication between industrial devices and  
CANopen networks*

## Features and benefits

# Anybus CompactCom 30 Module CANopen without housing



## General

Net Width (mm)	37
Net Height (mm)	16
Net Depth (mm)	51
Net Weight (g)	18
Packed Weight (g)	18
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	A
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8-bit parallel (30 ns access) UART (max 625kbps)
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M30 module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1

## Identification and Status

Product ID	AB6318-B
Successor	AB6713-C
Country of Origin	Sweden

# Anybus CompactCom 30 Module CANopen without housing



## Identification and Status

HS Code	8517620000
Export Control Classification Number (ECCN)	3A991.a.2

## Physical Features

Connectors / Input / Output	D-sub
LED Indicators	Indicates Module Status and Network Status.
Form Factor	Module without Housing

## Certifications and Standards

Protection Class IP	IP20
UL Information	E214107