

Anybus X-gateway – Interbus FO Slave - PROFIBUS Slave

Item number: AB7848-F

The Anybus X-gateway Interbus FO Slave to PROFIBUS Slave enables you to connect any Interbus FO system to any PROFIBUS control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



A protocol converter that connects Interbus FO and PROFIBUS control systems

Features and benefits

- ✓ **Reach new markets**
Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- ✓ **Slim hardware design**
The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **Easy configuration – No programming required!**
Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- ✓ **Trusted partner**
Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.
- ✓ **No PLC card slot needed**
The gateway does not use a card slot in the control system, leaving room for other equipment.
- ✓ **3-year warranty**
The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✓ **Increased PLC performance**
The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.
- ✓ **Life cycle management**
HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.
- ✓

Anybus X-gateway – Interbus FO Slave - PROFIBUS Slave



Identification and Status

Product ID	AB7848-F
Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	5A991.b.3

General

Net Width (mm)	44
Net Height (mm)	127
Net Depth (mm)	114
Net Weight (g)	400
Packed Width (mm)	17
Packed Height (mm)	9
Packed Depth (mm)	19
Packed Weight (g)	600
Operating Temperature °C Min	-25
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	400mA @ 24V DC
Input Voltage (V)	24V DC (-20% to +20%)

Anybus X-gateway – Interbus FO Slave - PROFIBUS Slave



General

Power Connector	2-pin, 5.08 Phoenix plug connector
Isolation	TRUE
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Aluminum, Plastic
Packaging Material	Cardboard

Physical Features

Connectors / Input / Output	1x D-sub 9-pin female PROFIBUS connector, 1x HFBR-2505C and 1x HFBR-1505C Fiber Optic network connectors, USB-B Config port
DIP & Rotary Switches	2x Rotary Address Node

INTERBUS Features

INTERBUS Mode	Slave
INTERBUS Supported Functionality	EN 50170; Fiber Optic conform to IEC874-2 and DIN47258; Transmission Media: Plastic fibre, core 980um, clad 1000um: HCS (glass) fibre, core 200um, clad 230 um;PCP V.2.0. (0, 1, 2, or 4 words);Automatic slave address detection
INTERBUS Baud Rate	500 kbit/s – 2 Mbit/s
INTERBUS Input Data Size	20 bytes of process data (512 bytes with PCP)
INTERBUS Output Data Size	20 bytes of process data (512 bytes with PCP)

PROFIBUS Features

PROFIBUS Mode	DP Device
PROFIBUS Supported Functionality	PROFIBUS-DP/DPV1 Slave functionality according to extensions of EN 50170; Acyclic Communication (DP-V1, Class 1 & 2); Acyclic User Parameter data / Diagnostics length - up to 237 bytes; Sync; Freeze; Watchdog
PROFIBUS Device Address	0-125
PROFIBUS Configuration File	GSD available
PROFIBUS Baud Rate	9600 bit/s - 12 Mbit/s
PROFIBUS Input Data Size	244 bytes (344 max tot in+out)
PROFIBUS Output Data Size	244 bytes (344 max tot in+out)

Anybus X-gateway – Interbus FO Slave - PROFIBUS Slave



Certifications and Standards

Protection Class IP	IP20
Recycle / Disposal	TRUE
UL Information	E214107: Ord.Loc UL508, CSA C22.2 NO. 142
Environment	EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment