

Anybus CompactCom 30 Module USB

Item number: AB6209-B

The Anybus CompactCom 30 USB is a passive module that acts as a physical layer converter for USB communication. As a passive module, it doesn't process the serial bitstream. This module enables a transparent USB channel using the Anybus CompactCom slot. The module uses the serial channel of the application interface.



Enables transparent USB communication

Features and benefits



Identification and Status

Product ID	AB6209-B
Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	3A991.a.2

General

Net Width (mm)	50
Net Height (mm)	22
Net Depth (mm)	52
Net Weight (g)	22
Packed Weight (g)	22
Operating Temperature °C Min	-40
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	A
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	RxD/TxD
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M30 Passive module
Mounting	PCB mounting via a customized CompactFlash connector

Anybus CompactCom 30 Module USB



General

Warranty (years)	1
------------------	---

Physical Features

Connectors / Input / Output	USB
-----------------------------	-----

LED Indicators	Power
----------------	-------

Form Factor	Module
-------------	--------

Certifications and Standards

Protection Class IP	IP20
---------------------	------

UL Information	E214107
----------------	---------