

Anybus ProfiHub B5+

Item number: 17020R

For PROFIBUS network designs, the ProfiHub B5+ offers a reliable and robust backbone solution with robust message checking and selectable redundancy on communication and power supply.



Efficient network segmentation with integrated diagnostics down to the last device

Features and benefits

Diagnostics slave device
Capability to show diagnostic messages down to the last

device with ComBricks

Compatible with different application speeds
The repeater is transparent and handles a connection speed from 9.6Kbps to 12Mbps easily

Network segmentation

Increase network reliability by creating isolated segmentations



Anybus ProfiHub B5+



| Identification and Status | |
|--|-----------------------|
| Product ID | 17020R |
| Country of Origin | Netherlands (the) |
| HS Code | 8471800000 |
| Export Control Classification Number (ECCN) | EAR99 |
| General | |
| Net Width (mm) | 167 |
| Net Height (mm) | 113 |
| Net Depth (mm) | 35 |
| Net Weight (g) | 660 |
| Packed Width (mm) | 16 |
| Packed Height (mm) | 6 |
| Packed Depth (mm) | 26 |
| Packed Weight (g) | 664 |
| Operating Temperature °C Min | -25 |
| Operating Temperature °C Max | 70 |
| Current Consumption Type Value at Vcc Nom (mA) | 275 mA |
| Current Consumption Max value at Vcc nom (mA) | 275 mA |
| Input Voltage (V) | 931 VDC |
| Power Wire Diameter (mm) | < 2.5 mm ² |
| Warranty (years) | 1 Year |



Anybus ProfiHub B5+



Certifications and Standards Protection Class IP IP20 WEEE Category IT and telecommunications equipment

