



Anybus ComBricks 1 Channel RS485 SCOPE Repeater

Item number: 101-201410C

The RS 485-IS barrier is the only available product for remotely monitoring IS segments over Ethernet from the safe zone.



Enables access to IS zones within your network remotely

Features and benefits

✓ **Meets all expectations**

It complies with the specifications for PROFIBUS DP in IS segments and drives 31 RS 485-IS PROFIBUS DP devices.

✓ **Integrated oscilloscope**

Anybus ProfiTrace and an Oscilloscope are integrated and also suitable for Intrinsic Safety.

Anybus ComBricks 1 Channel RS485 SCOPE Repeater



General

Net Weight (g)	187
Packed Width (mm)	6
Packed Height (mm)	14
Packed Depth (mm)	20
Packed Weight (g)	265
Operating Temperature °C Min	-20
Operating Temperature °C Max	60
Current Consumption Type Value at Vcc Nom (mA)	450 mA
Current Consumption Max value at Vcc nom (mA)	750 mA
Power Wire Diameter (mm)	< 2.5 mm ²
Mounting	DIN rail mount (bracket included)
Housing Materials	Plastic
Packaging Material	Cardboard
Warranty (years)	1 Year

Identification and Status

Product ID	101-201410C
Country of Origin	Netherlands (the)
HS Code	8471800000
Export Control Classification Number (ECCN)	EAR99

Certifications and Standards

Protection Class IP	IP20
---------------------	------

Anybus ComBricks 1 Channel RS485 SCOPE Repeater



Certifications and Standards

WEEE Category	IT and telecommunications equipment
---------------	-------------------------------------