

Panasonic Air to Water (Aquarea H/J) to Modbus RTU Interface

Item number: INMBSPAN001A000

The Panasonic-Modbus interface allows full bidirectional communication between Panasonic Air to Water (Aquarea H/J) units and Modbus RTU (RS-485) networks. The interface acts as a server device for the installation, accessing all signals from the Air to Water unit.



Panasonic Air to Water to Modbus RTU - 1 AW unit

Features and benefits

- ✓ **Modbus RTU (EIA-485) server device**
The interface acts as a Modbus server device through its Modbus RTU (EIA-485 connector) port.
- ✓ **Energy savings through a window contact function**
This function helps minimize costs, as HVAC systems are a major building energy consumer.
- ✓ **AC unit control by both the remote and Modbus RTU**
The AC unit can be simultaneously controlled by the manufacturer's remote controller and Modbus RTU.
- ✓ **Multiple mounting options**
Mounting options include DIN rail, wall, or, in some AC models, even inside the indoor unit.
- ✓ **Dual configuration options**
Configuration is carried out through the interface's onboard DIP switches and the Modbus interface.
- ✓ **Total unit control and monitoring from Modbus RTU**
Through internal variables, running hours counter (for maintenance purposes), and error indication.
- ✓ **No external power required**
The interface is powered directly from the AC unit, so no external power supply is required.

Panasonic Air to Water (Aquarea H/J) to Modbus RTU Interface



Identification and Status

| | |
|---|-----------------|
| Product ID | INMBSPAN001A000 |
| Country of Origin | Spain |
| HS Code | 8517620000 |
| Export Control Classification Number (ECCN) | EAR99 |

General

| | |
|------------------------------|--|
| Net Width (mm) | 53 |
| Net Height (mm) | 58 |
| Net Depth (mm) | 93 |
| Net Weight (g) | 160 |
| Operating Temperature °C Min | 0 |
| Operating Temperature °C Max | 60 |
| Input Voltage (V) | From the unit. |
| Power Connector | Other |
| Capacity | 1 Air-to-Water unit. |
| Installation Conditions | This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit. |
| Content of Delivery | Intesis gateway and installation manual. |
| Mounting | DIN rail mount (bracket included), Wall mount |
| Housing Materials | Plastic |
| Warranty (years) | 3 years |
| Packaging Material | Cardboard |

Panasonic Air to Water (Aquarea H/J) to Modbus RTU Interface



Physical Features

| | |
|------------------------------------|-------------------|
| Connectors / Input / Output | EIA-485, AC port. |
|------------------------------------|-------------------|

Certifications and Standards

| | |
|----------------------------|----------|
| ETIM Classification | EC001604 |
|----------------------------|----------|


| | |
|----------------------|-------------------------------------|
| WEEE Category | IT and telecommunications equipment |
|----------------------|-------------------------------------|



Use Case

Panasonic

Modbus



Integration example.