

Ixxat USB-to-CAN FD compact

Item number: 1.01.0351.12001

The Ixxat USB-to-CAN FD compact with a D-Sub 9 CAN/CAN FD interface and galvanic isolation is an easy and cost-efficient way to connect a computer to a CAN/CAN FD bus network. It enables simple integration into diverse industrial setups, supporting various CAN applications, from testing and development to maintenance and control tasks.



PC interface adapter (1 x CAN FD), galv. isolated

Features and benefits

- ✓ **Versatile connectivity for CAN-based networks**
Simplifies the connection of computers to CAN-based networks by providing versatile integration options for industrial and automotive applications.
- ✓ **Powerful CAN FD connection**
Equipped with a CAN FD channel (up to 8 Mbits) via a RJ45 socket for rapid and reliable data communication in CAN/CAN FD networks.
- ✓ **High-precision timestamps**
High-precision on-board time-stamping allows for precise data tracking and monitoring.
- ✓ **Overvoltage protection**
Galvanic isolation safeguards against overvoltage and protects from potential electrical damage.
- ✓ **Powerful programming interface**
Ixxat offers versatile programming interfaces for Windows (VCI), Linux (ECI) and real-time OS (on request), enabling flexible development across multiple operating systems.
- ✓ **Cost-effective connectivity**
Offers a cost-effective solution, delivering high performance at an economical price. Ideal choice for demanding applications, without having to compromise on quality.
- ✓ **High-speed USB connectivity**
Native USB 2.0 hi-speed (480 MBit/s) ensures fast data transfer and compatibility with USB 3.x.
- ✓ **Efficient data handling**
Offers high data throughput combined with minimal latency, ensuring prompt and efficient data processing for demanding needs.
- ✓ **Comprehensive driver compatibility**
Ixxat VCI driver packages support multiple fieldbuses and allow easy switching between different PC interface types. Available as free download.
- ✓ **Analysis software included**
Ixxat canAnalyser3 Mini is included in the VCI V4 download package and enables first steps in analyzing and monitoring CAN networks.



Identification and Status

Product ID	1.01.0351.12001
Country of Origin	Germany
HS Code	8517620000
Export Control Classification Number (ECCN)	EAR99

General

Net Width (mm)	50
Net Height (mm)	80
Net Depth (mm)	22
Net Weight (g)	100
Packed Width (mm)	14
Packed Height (mm)	4
Packed Depth (mm)	18
Packed Weight (g)	239
Operating Temperature °C Min	-20
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	10 to 95 %, non-condensing
Current Consumption Type Value at Vcc Nom (mA)	32 mA
Current Consumption Max value at Vcc nom (mA)	300 mA (5 V DC)

Ixxat USB-to-CAN FD compact



General

Input Voltage (V)	5 V DC via USB port
Power Connector	USB
Isolation	800 V DC/ 500 V AC for 1 min.
Content of Delivery	USB-to-CAN FD interface, user manual, available as free download: CAN driver VCI, simple CAN monitor "canAnalyser Mini"
Not Included (in delivery)	Comprehensive and powerful driver and software packages are available as free download
Housing Materials	PC ABS, UL 94 VO
Packaging Material	Cardboard
Warranty (years)	1

Physical Features

Connectors / Input / Output	1 x D-Sub 9 connector, 1 x USB type A connector
------------------------------------	---

CAN Features

CAN Mode	CAN high-speed (ISO 11898-2: 2016)
CAN Controller	IFI CAN_FD IP/80 MHz
CAN Baud Rate	10 kbit/s to 1 Mbit/s

CAN FD Features

CAN FD Mode	ISO CAN FD (ISO 11898-1: 2015), nonISO CAN FD
CAN FD Transceiver	MCP2562FDT
CAN FD Baud Rate	Arbitration rate up to 1000 kBit/s, data rate up to 8000 kBit/s (verified by testing). User defined bit rates are possible.

Certifications and Standards

Protection Class IP	IP40
ETIM Classification	EC000515
WEEE Category	IT and telecommunications equipment