



Anybus CompactCom 30 Brick EtherNet/IP 2 port

Item number: AB6384-B

The Anybus CompactCom 30 EtherNet/IP 2-Port is a communication interface that can be embedded into any industrial device or machine to enable communication with EtherNet/IP networks. The brick version is fully embedded into the industrial device and is the best choice if you have limited space or need a specific connector or protection class.



Enable communication between industrial devices and EtherNet/IP 2-port networks

Features and benefits

Anybus CompactCom 30 Brick EtherNet/IP 2 port



General

Net Width (mm)	50
Net Height (mm)	22
Net Depth (mm)	52
Net Weight (g)	15
Packed Weight (g)	15
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	B
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8-bit parallel (30 ns access) UART (max 625kbps)
Isolation	Galvanic Isolation
Content of Delivery	CompactCom B30 module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1

Identification and Status

Product ID	AB6384-B
Country of Origin	Sweden
HS Code	8517620000

Anybus CompactCom 30 Brick EtherNet/IP 2 port



Identification and Status

Export Control Classification Number (ECCN)	3A991.a.2
Supply Risk Factor ERP	Volume not defined yet

Physical Features

Connectors / Input / Output	M12
LED Indicators	Indicates Module Status and Network Status.
Form Factor	Brick (pluggable)

Certifications and Standards

Protection Class IP	IP20
UL Information	E214107