


## Ixxat fieldbus expansion CAN LS

Item number: 1.01.0241.20001

The fieldbus expansion board for the Ixxat CAN-IB series enhances the card's capabilities with an additional low-speed CAN option. Acting as a piggy-back module, each existing CAN high-speed channel can be equipped with a separate expansion board, making it an effective solution for systems requiring versatile fieldbus communications.



*Piggyback module for CAN interface cards*

### Features and benefits

- ✓ **Enhanced protocol support**  
Adds CAN low-speed functionality to the system, supporting the integration of diverse fieldbus protocols for comprehensive connectivity.
- ✓ **Modular design**  
Either one or two fieldbus expansions can be used per CAN interface or CAN expansion board, providing flexibility for specific requirements.
- ✓ **Overvoltage protection**  
Galvanic isolation safeguards against overvoltage and protects from potential electrical damage.
- ✓ **Easy installation and compatibility**  
Designed as a piggy-back module for both PC interface cards and CAN expansion boards, enabling an efficient setup without extensive system modifications.
- ✓ **Switchable CAN high- and low-speed channels**  
Each existing high-speed CAN channel can be switched to low-speed CAN through software, providing flexibility for future requirements.



General	
Net Width (mm)	25
Net Height (mm)	47
Net Weight (g)	6
Packed Width (mm)	14
Packed Height (mm)	4
Packed Depth (mm)	18
Packed Weight (g)	69
Operating Temperature °C Min	0
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	10 to 95 %, non-condensing
Input Voltage (V)	3.3 V DC via CAN interface board
Isolation	500 V AC for 1 min. between CAN bus and internal logic
Content of Delivery	Expansion board, user manual
Mounting	PCB mounting
Packaging Material	Cardboard
Warranty (years)	1
Identification and Status	
Product ID	1.01.0241.20001



## Identification and Status

Country of Origin	Germany
HS Code	8517620000
Export Control Classification Number (ECCN)	EAR99
Supply Risk Factor ERP	Volume not defined yet

## Physical Features

Connectors / Input / Output	3 x box header connector
-----------------------------	--------------------------

## CAN Features

CAN Mode	CAN low-speed (ISO 11898-3)
CAN Transceiver	NXP TJA1054
CAN Baud Rate	CAN low-speed: 10 kBit/s to 125 kBit/s

## Certifications and Standards

ETIM Classification	EC001604
WEEE Category	IT and telecommunications equipment