

Anybus CompactCom 40 Module Without Housing - Common Ethernet - Transparent Ethernet



Item number: AB6734-E

The Anybus CompactCom 40 Common Ethernet is a communication interface that can be embedded into any industrial device or machine to enable communication with PROFINET, EtherCAT, EtherNet/IP, Modbus TCP, Powerlink, or BACnet/IP networks. The Transparent Ethernet channel lets you utilize high-end processors for custom IT functions. With connectors.

Enable communication between industrial devices and Industrial Ethernet networks

Features and benefits

- ✓ **High performance**
Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.
- ✓ **Quick time to market**
HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.
- ✓ **Life cycle management**
HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.
- ✓ **Easy to install**
Installing the Anybus CompactCom module is a breeze—simply slide it into the host slot. This user-friendly process can be completed by the end-user.
- ✓ **Transparent Ethernet channel**
Includes a Transparent Ethernet channel, allowing users to tap into the potential of their high-end processors for developing personalized IT functions.
- ✓ **Versatile Event-Based Hardware Interfaces**
Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.
- ✓ **Pre-certified**
Pre-certified for network compliance for all networks, enabling faster network certification.
- ✓ **Complete communication interface**
The Anybus CompactCom module is a complete communication interface, equipped with connectors that simplify integration. Enjoy an all-in-one solution with easy interchangeability.
- ✓ **Robust Security Measures**
Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.
- ✓ **Switch networks without changing hardware**
Simply download firmware for PROFINET, EtherCAT, Modbus-TCP, POWERLINK, or EtherNet/IP, ensuring adaptability to industrial network changes without altering hardware.

Anybus CompactCom 40 Module Without Housing - Common Ethernet - Transparent Ethernet



General	
Net Width (mm)	37
Net Height (mm)	16
Net Depth (mm)	51
Net Weight (g)	18
Packed Weight (g)	18
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	B
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8/16-bit parallel (30 ns access) High speed SPI, baudrate configurable up to 20 MHz I/O (shift register interface, cyclical update time 82 µs) UART (for backwards compatibility with 30-series, max 625kbps)
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M40 module (without housing)
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1 year
Identification and Status	
Product ID	AB6734-E
Country of Origin	Sweden
HS Code	8517620000

Anybus CompactCom 40 Module Without Housing - Common Ethernet - Transparent Ethernet



Identification and Status

Export Control Classification Number (ECCN)	3A991.a.2
--	-----------

Physical Features

Connectors / Input / Output	2x RJ45
------------------------------------	---------

LED Indicators	Semi-Integrated. Link/Activity are available on RJ45 connectors. Module Status and Network Status via application interface or external light pipes
-----------------------	---

Form Factor	Module without Housing
--------------------	------------------------

Certifications and Standards

UL Information	E214107
-----------------------	---------