



## Ixxat CAN termination

Item number: 1.04.0075.02000

The Ixxat CAN termination is equipped with a D-Sub 9 male connector and a 120 Ohm resistor, ensuring proper termination of CAN and CAN FD buses. It is used when a CAN node lacks internal termination or if no CAN node is connected at the end of the CAN bus. Per ISO 11898-2, high-speed CAN systems require end resistors.

*Termination for CAN/CAN FD networks (D-Sub 9 plug)*

### Features and benefits

- ✓ **Optimal signal integrity**  
Integrates a 120 Ohm resistor, ensuring proper CAN/CAN FD bus termination. The resistor is placed between pin 2 (CAN-L) and pin 7 (CAN-H).
- ✓ **Convenient integration**  
Features a direct 1-to-1 pin assignment, making connection straightforward.
- ✓ **Universal compatibility**  
Comes with a 9-pin male D-Sub plug, fitting standard CAN interfaces.
- ✓ **Technical data overview**  
Insulator: PBT glass fiber reinforced / contact: brass, gold plated over nickel / shell: tin plated / insulator resistance: 500 MOhm min. at 500 V DC / temperature range: -55 °C to 105 °C



## General

Net Weight (g)	30
----------------	----

Packed Weight (g)	30
-------------------	----

## Identification and Status

Product ID	1.04.0075.02000
------------	-----------------

Country of Origin	China
-------------------	-------

HS Code	8536901000
---------	------------

Export Control Classification Number (ECCN)	EAR99
---	-------

## Certifications and Standards

ETIM Classification	EC002584
---------------------	----------

WEEE Category	IT and telecommunications equipment
---------------	-------------------------------------