

## Anybus Wireless Bolt Serial - White version

Item number: AWB2011-B

The Anybus Wireless Bolt Serial - White connects serial machines to wireless networks via Bluetooth<sup>®</sup> or Wi-Fi. Designed for multi-directional applications, it's ideal for establishing wireless connections with roaming machines, such as AGVs or control cabinets from any angle. It also works as a Modbus-TCP to Modbus-RTU router.



*Connect serial machines in multi-directional applications via Bluetooth or Wi-Fi*

### Features and benefits

- ✓ **Low total cost of ownership**  
Thanks to the integrated design of the antenna and communication module, there's no need for additional antenna or accessory purchases.
- ✓ **Modbus protocol routing**  
Works as a router for Modbus-TCP to Modbus-RTU enabling transparent access to all your existing serial Modbus devices.
- ✓ **Easy access to data**  
Wirelessly connect to the Anybus Bolt and easily access the machine or cabinet. Configure the PLC or machine without halting or hindering production.
- ✓ **All-in-one wireless communication**  
All-in-one package featuring a connector, communication processor, and integrated antenna in the same unit.
- ✓ **Industrial design**  
Withstands harsh environments due to its IP66/67-rated enclosure and wide operating temperature range. Choose the white top Sunbolt option for 30% better protection against higher temperatures.
- ✓ **Easy to configure**  
Establish a wireless connection in seconds thanks to the intuitive web-based interface.
- ✓ **Serial to TCP/IP data conversion**  
Converts RS232/RS485 data to TCP/IP data.
- ✓ **Access Point in multi-point applications**  
The versatile Bolt can function as an Access Point in multi-point applications, facilitating connections for up to seven clients simultaneously.
- ✓ **Quick start up and high determinism**  
Ideal for connecting field-level devices that require short start-up times and high determinism.
- ✓ **Perfect together!**  
Fully compatible with Anybus Wireless Bridge, a wireless product designed for point-to-point applications, enabling you to implement comprehensive wireless infrastructure.
- ✓ **Easy to install**  
Attach the Wireless Bolt directly onto cabinets or machines to look like an integrated part of the installation. Or use the Bolt Base Protector mounting kit to install it on a pole, wall, or similar.
- ✓ **Insights into your network**  
The Command Line Interface (CLI) provides configuration and diagnostic capabilities, offering greater control and insight into your network.

# Anybus Wireless Bolt Serial - White version



## General

Net Weight (g)	85
Net Dimensions (mm)	68 x 75 (Ø X H) Height above mounting surface: 42.
Packed Width (mm)	13
Packed Height (mm)	8
Packed Depth (mm)	12
Packed Weight (g)	185
Operating Temperature °C Min	-40
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Power Consumption (W)	1.7
Input Voltage (V)	9-30
Power Connector	3-pole
Housing Materials	Plastic
Packaging Material	Cardboard

## Identification and Status

Product ID	AWB2011-B
Model Code	AWB2AB
Country of Origin	Sweden
HS Code	8517620000

# Anybus Wireless Bolt Serial - White version



## Identification and Status

Export Control Classification Number (ECCN)	5A992.c
---	---------

## Physical Features

Connectors / Input / Output	18-pin connection
-----------------------------	-------------------

## Wi-Fi Features

Operation Mode	Access Point, Client
RF Output Power	18 dBm EIRP (including antenna gain 3dBi)
Max No. Of Connections, Access Point	7
Security	WPA2 Personal; WPA2 Enterprise
Net Data Throughput	20 Mbps

## Bluetooth Features

Operation Mode	Access Point, Client
Max No. Of Connections	7
Bluetooth Version	Classic Bluetooth v2.1
Net Data Throughput	20 Mbps

## Bluetooth Low Energy Features

Operation Mode (LE)	Access Point, Client
RF Output Power (LE)	14 dBm EIRP (including max antenna gain 3 dBi)
Max No. Of Connections (LE)	7
Bluetooth Version (LE)	Bluetooth v4.0
Net Data Throughput (LE)	1Mbps

## Certifications and Standards

Protection Class IP	IP66, IP67
---------------------	------------

### Vibration and Shock

Sinosoidal vibration test according to IEC 60068-2-6:2007 and with extra severities; Number of axes: 3 mutually perpendicular (X:Y:Z), Duration: 10 sweep cycles in each axes, Velocity: 1 oct/min, Mode: in operation, Frequency: 5-500 Hz, Displacement  $\pm 3.5$  mm, Acceleration: 2g. Shock test according to IEC 60068-2-27:2008 and with extra severities; Wave shape: half sine, Number of shocks:  $\pm 3$  in each axes, Mode: In operation, Axes  $\pm X,Y,Z$ , Acceleration: 30 m/s<sup>2</sup>, Duration: 11





## Certifications and Standards

WEEE Category	IT and telecommunications equipment
---------------	-------------------------------------