



Ixxat CAN-IB600/PCIe

Item number: 1.01.0233.22010

The Ixxat CAN-IB600/PCIe is an active PCI Express interface card with two CAN/CAN FD channels and galvanic isolation. It is an easy and cost-efficient way to connect computers to a CAN/CAN FD bus network. Based on a modular design, the card enables simple integration into diverse industrial setups, supporting various CAN applications.

PC interface card for CAN FD (2 x CAN FD), galv. isolated

Features and benefits

- ✓ **Active CAN interface card**
Fulfills even high requirements in data pre-processing, like precise on-board time-stamping and data filtering.
- ✓ **PCle interface**
Single-lane (1x) PCI Express interface supports high-speed data transmission, ideal for demanding industrial applications.
- ✓ **Switchable CAN/CAN FD channels**
Equipped with two switchable CAN/CAN FD channels to send and receive ISO CAN FD, non-ISO CAN FD or CAN2.0A/B messages, offering fast data transmission and high flexibility.
- ✓ **Modular architecture for easy expansion**
Modern and modular concept enables easy extension with customer specific interfaces via expansion boards and piggyback modules.
- ✓ **Overvoltage protection**
Galvanic isolation safeguards against overvoltage and protects from potential electrical damage.
- ✓ **Powerful programming interface**
Ixxat offers versatile programming interfaces for Windows (VCI), Linux (ECI) and real-time OS (on request), enabling flexible development across multiple operating systems.
- ✓ **Cost-effective connectivity**
Offers a cost-effective solution, delivering high performance at an economical price. Ideal choice for demanding applications, without having to compromise on quality.
- ✓ **Use in industrial and standard PCs**
PC board with slot plate for fixed installation in desktop or industrial PCs, providing reliable connectivity.
- ✓ **Installation of multiple cards**
Integration of multiple cards in one PC allows easy channel extension, making it suitable even for demanding settings like test benches and manufacturing plants.
- ✓ **Expandable LIN and low-speed CAN channel**
Supports expansion boards for additional low-speed CAN or LIN channel – switchable through software (CAN).
- ✓ **Comprehensive driver compatibility**
Ixxat VCI driver packages support multiple fieldbuses and allow easy switching between different PC interface types. Available as free download.
- ✓ **Analysis software included**
Ixxat canAnalyser3 Mini is included in the VCI V4 download package and enables first steps in analyzing and monitoring CAN networks.



| General | |
|--|---|
| Net Width (mm) | 69 |
| Net Height (mm) | 105 |
| Net Weight (g) | 190 |
| Packed Width (mm) | 17 |
| Packed Height (mm) | 5 |
| Packed Depth (mm) | 13 |
| Packed Weight (g) | 195 |
| Operating Temperature °C Min | 0 |
| Operating Temperature °C Max | 70 |
| Storage Temperature °C Min | -40 |
| Storage Temperature °C Max | 85 |
| Relative Humidity | 10 to 95 %, no condensation |
| Current Consumption Type Value at Vcc Nom (mA) | 400 mA (3.3 V DC) |
| Input Voltage (V) | 3.3 V DC via PCIe socket |
| Power Connector | PCIe socket (3.3 V / 12 V DC) |
| Isolation | 1 kV DC for 1 sec. |
| Content of Delivery | PC interface card, user manual, available as free download: CAN driver VCI, simple CAN monitor "canAnalyser Mini" |
| Not Included (in delivery) | Comprehensive and powerful driver and software packages are available as free download |
| Mounting | PCI Express |



General

| | |
|--------------------|-----------|
| Packaging Material | Cardboard |
| Warranty (years) | 1 |

Identification and Status

| | |
|---|-----------------|
| Product ID | 1.01.0233.22010 |
| Country of Origin | Germany |
| HS Code | 8517620000 |
| Export Control Classification Number (ECCN) | EAR99 |

Physical Features

| | |
|-----------------------------|--|
| Connectors / Input / Output | 2 x D-Sub 9 connector, 1 x PCI express (V1.1), single lane port (x1) |
|-----------------------------|--|

CAN Features

| | |
|-----------------|---|
| CAN Mode | CAN high-speed (ISO 11898-2), via optional expansion: CAN low-speed (ISO 11898-3) |
| CAN Transceiver | TI SN65HVD251 |
| CAN Controller | CAN 2.0 A/B |
| CAN Baud Rate | CAN high-speed: 10 kBit/s to 1 Mbit/s, via optional expansion: CAN low-speed: 10 kBit/s to 125 kBit/s |

CAN FD Features

| | |
|------------------|---|
| CAN FD Mode | ISO CAN FD, nonISO CAN FD |
| CAN FD Baud Rate | Arbitration rate up to 1000 kBit/s, data rate up to 8000 kBit/s (verified by testing). User defined bit rates are possible. |

LIN Features

| | |
|----------|--|
| LIN Mode | via optional expansion: LIN (ISO 9141) |
|----------|--|

Certifications and Standards

| | |
|---------------------|-------------------------------------|
| ETIM Classification | EC000515 |
| WEEE Category | IT and telecommunications equipment |